


LE-Series


LED-backlit Display 27" | 24" | 22"

Ergonomic Displays for Home and Diverse Business Environments



The LE-Series is crafted with comfort and efficiency in mind. Its ergonomically-designed stand allows multiple viewing options, while its low blue light filter and flicker-free backlight ensure a comfortable viewing experience. Multiple connectivity options—DisplayPort, HDMI, and VGA—enable a wealth of multimedia applications and flexibility of connections. Various preset picture modes and colour settings are provided for different screen applications both at the workplace and in the home.





Maximized Comfort and Efficiency

An ergonomically-designed stand makes it possible to configure your workstation and create a working environment the way you want it. For comfort, convenience, and efficiency, tilt, pivot, or swivel the display, adjust its height, or shift to either portrait or landscape mode.

Eye Comfort

Eye comfort figures high on the list of strengths that define the LE-Series. The flicker-free backlight and blue light filter of the LE-Series ensure a comfortable viewing experience by reducing eyestrain after long periods of use.



LOW BLUE LIGHT



Flexible Connectivity and Multimedia Options

Connectivity versatility brings immense flexibility. Given its HDMI, DisplayPort, and VGA input options, you can easily connect an LE-Series display to your current or older peripherals, like PCs, laptops, or media players and enjoy Full HD resolution video and audio content.

Features

- Full HD 1920 x 1080 resolution
- Height adjustable stand allows users to tilt, pivot and swivel
- Blue-light filter and Flicker-free display technology reduces eye discomfort
- Versatile connectivity: DisplayPort, HDMI, VGA
- VESA mount compatibility for flexible installation



Specifications

LE-27E

LE-24E

LE-22E

Specifications		LE-27E	LE-24E	LE-22E
Panel	Panel Type	LED-Backlit TFT LCD (TN Technology)	LED-Backlit TFT LCD (TN Technology)	LED-Backlit TFT LCD (TN Technology)
	Panel Size	27.0"	23.5"	21.5"
	Max. Resolution	FHD 1920 x 1080	FHD 1920 x 1080	FHD 1920 x 1080
	Pixel Pitch	0.311 mm	0.272 mm	0.248 mm
	Brightness	300 cd/m ²	250 cd/m ²	250 cd/m ²
	Contrast Ratio	20,000,000:1 (DCR)	20,000,000:1 (DCR)	20,000,000:1 (DCR)
	Viewing Angle (H/V)	170°/160°	170°/160°	170°/160°
	Display Colour	16.7M	16.7M	16.7M
	Response Time	3 ms	3 ms	3 ms
Frequency (H/V)	H Freq.	30 kHz-95 kHz	30 kHz-95 kHz	30 kHz-95 kHz
	V Freq.	48 Hz-76 Hz	48 Hz-76 Hz	48 Hz-76 Hz
Input	DisplayPort	x 1	x 1	x 1
	HDMI	1.4 x 1	1.4 x 1	1.4 x 1
	VGA	15-Pin D-Sub x 1	15-Pin D-Sub x 1	15-Pin D-Sub x 1
Audio	Audio In	Stereo Audio Jack (3.5 mm)	Stereo Audio Jack (3.5 mm)	Stereo Audio Jack (3.5 mm)
	Audio Out	Stereo Audio Jack (3.5 mm)	Stereo Audio Jack (3.5 mm)	Stereo Audio Jack (3.5 mm)
	Internal Speakers	2W x 2	2W x 2	2W x 2
Power	Power Supply	Internal	Internal	Internal
	Power Requirement	AC 100-240V, 50/60 Hz	AC 100-240V, 50/60 Hz	AC 100-240V, 50/60 Hz
	On Mode	26W (On)	19W (On)	19W (On)
	Stand-by Mode	< 0.5W	< 0.5W	< 0.5W
Operating Conditions	Temperature	0°C-40°C (32°F-104°F)	0°C-40°C (32°F-104°F)	0°C-40°C (32°F-104°F)
	Humidity	10%-85% (non-condensing)	10%-85% (non-condensing)	10%-85% (non-condensing)
Storage Conditions	Temperature	-20°C-60°C (-4°F-140°F)	-25°C-55°C (-13°F-131°F)	-25°C-55°C (-13°F-131°F)
	Humidity	5%-90% (non-condensing)	10%-85% (non-condensing)	10%-85% (non-condensing)
Mounting	VESA FPM PMI	Yes (100 x 100 mm)	Yes (100 x 100 mm)	Yes (100 x 100 mm)
Stand	Tilt	-5° to 23°	-5° to 23°	-5° to 23°
	Pivot	-2.5° to 92.5°	-2.5° to 92.5°	-2.5° to 92.5°
	Swivel	± 70°	± 70°	± 70°
	Height Adjustment	0-110 mm	0-110 mm	0-110 mm
Security	Kensington Security Slot	Yes	Yes	Yes
Dimensions	w/Base (W x H x D)	642.0 x 533.7 x 249.0 mm (25.3" x 21.0" x 9.8")	566.0 x 510.2 x 249.0 mm (22.3" x 20.1" x 9.8")	505.6 x 494.7 x 248.9 mm (19.9" x 19.5" x 9.8")
	Packaging (W x H x D)	758.0 x 478.0 x 312.0 mm (29.8" x 18.8" x 12.3")	655.0 x 445.0 x 297.0 mm (25.8" x 17.5" x 11.7")	590.0 x 415.0 x 282.0 mm (23.2" x 16.3" x 11.1")
Weight	w/Base	7.5 kg (16.5 lb)	5.8 kg (12.8 lb)	5.4 kg (11.9 lb)
	Packaging	10.1 kg (22.2 lb)	8.3 kg (18.3 lb)	7.5 kg (16.5 lb)
Regulation Approval	Certification & Compliance	FCC, CE, CB, BSMI, WEEE, RoHS, REACH, EAC	FCC, CE, CB, BSMI, WEEE, RoHS, REACH, EAC	FCC, CE, CB, BSMI, WEEE, RoHS, REACH, EAC
Accessories	Supplied	Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card
Optional Accessories		Wall Mount: PMK-01 Desk Mounts: DMC-01 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mounts (Landscape only): WMA-01, WMK-01, WMK-03	Wall Mount: PMK-01 Desk Mounts: DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mounts (Landscape only): WMA-01, WMK-01, WMK-03	Wall Mount: PMK-01 Desk Mounts: DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mounts (Landscape only): WMA-01, WMK-01, WMK-03

Global Headquarters

Taipei, Taiwan

EMEA Regional Headquarters

Capelle a/d IJssel, The Netherlands

North & South America Regional Headquarters

San Jose, CA, U.S.A.

Asia-Pacific Regional Headquarters

Taipei, Taiwan

Canada Sales Office

Vancouver, B.C., Canada

China Sales Office

Shanghai, China

Czech Republic Sales Office

Brno, Czech Republic

Denmark Sales Office

Støvring, Denmark

Germany Sales Office

Mechernich, Germany

Italy Sales Office

Livorno, Italy

Poland Sales Office

Warsaw, Poland

Spain Sales Office

Barcelona, Spain

Ukraine Sales Office

Lviv, Ukraine

displays.agneovo.com