

Superior performance and value.

Crisp images. Eco-friendly. Affordably priced.

The days of limited monitor choices for a budget are over. The versatile ThinkVision® E2054 Monitor delivers superior performance and exceptional value. Ideal for mass deployments or where space-constraint areas, the 19.5" IPS wide-angle screen displays clear, crisp images from center to sides with a tilt-adjustable stand for comfortable viewing. It's certified Green, and connects seamlessly to most systems.



WHY YOU SHOULD BUY THE LENOVO™ THINKVISION® E2054 MONITOR




Superior screen performance

The 19.5" IPS panel delivers 1440 x 900 resolution with wide 178° / 178° viewing angles, displaying clear, crisp images from center to sides.



Versatility and productivity

Connect to any system with a VGA interface. The convenient tilt-adjustable stand suits any environment, or mount to a ThinkCentre® Tiny with a VESA® bracket.



Certified green

This eco-friendly monitor conforms to the latest Green standards including ENERGY STAR® 6.0, EPEAT™ Silver, TCO Display 6.0, CEL 1 and RoHs.

THE LENOVO™ THINKVISION® E2054 MONITOR IS BEST SUITED FOR

1

Businesses that need full, wide-screen monitors that can fit in limited desk space.

2

Customer-facing environments like receptions or cash desks that need superior display performance in a compact footprint.

3

IT managers seeking a versatile, affordably-priced monitor suitable for mass deployment.



SPECIFICATIONS

| DISPLAY | | MECHANICAL | |
|---|-------------------------------|---------------------------------------|---|
| Panel Size | 19.45" | Tilt Angle (Front / Back) | -5° ~ 22° |
| Panel Type | IPS | Swivel Angle (Left / Right) | No |
| Backlit | WLED | Lift (mm) | No |
| Viewable Area (Diagonal) | 19.45" | Pivot | No |
| Screen Dimensions (W x H) (mm) | 418.61 (H) x 262.35 (V) | VESA® Mount (mm) | 100 x 100 |
| Resolution | 1440 x 900 | Kensington® Lock Slot | Yes |
| Aspect Ratio | 16:10 | Cable Management | No |
| Viewing Angle (H/V at CR 10:1) | 178° / 178° | Ambient Light Sensor | No |
| Maximum Brightness (Typical) | 250 cd/m ² | Control Buttons | Yes |
| Contrast Ratio (Typical) | 1000:1 | Bezel Color | Raven Black |
| Dynamic Contrast Ratio | 3M:1 | Bezel Width | |
| Pixel Pitch (W x H) (mm) | 0.0969 x 0.2915 | Side (mm / inches) | 17.9 / 0.7" |
| Dot/Pixel Per Inch (DP / PPI) | 87.3 | Top (mm / inches) | 18 / 0.71" |
| Color Gamut (CIE 1931) | 72% | Bottom (mm / inches) | 26 / 1.02" |
| Number of Colors | 16.7 M | | |
| Response Time | 7 ms | | |
| Anti-Glare | Yes | | |
| SIGNAL INPUT | | SIGNAL INTERFACE / PERFORMANCE | |
| Video Input Signals | VGA | Horizontal Frequency | 30 kHz – 83 kHz |
| Video Cables Supplied | VGA | Vertical Frequency | 50 Hz – 75 Hz |
| Video Cable Length | 1.8 m | Native Resolution | 1440 x 900 |
| USB Hub | No | Maximum Pixel Clock Speed / Bandwidth | VGA: 205 MHz |
| USB Cable Supplied | No | Default Color Temperature | 7200K |
| | | Preset Display Modes | 18 |
| | | User-defined Display Modes | 10 |
| | | OSD Buttons | 5 |
| | | OSD Languages | 8 |
| POWER CONSUMPTION | | ENVIRONMENTAL | |
| Power Consumption | | Temperature | |
| Typical | 16 W | Operating | 0 °C – 45 °C (non-condensing) |
| Max. | 20 W | Non-operating | -20 °C – 60 °C (non-condensing) |
| Sleep-Mode | 0.5 W | Humidity | |
| Off-Mode | 0.5 W | Operating | 8% – 80% (non-condensing) |
| Heat Dissipation | | Non-operating | 5% – 95% (non-condensing) |
| Typical | 54.56 Btu/h | Altitude | |
| Max. | 68.2 Btu/h | Operating | 5,000 m |
| Power Supply | Internal | Non-operating | 40,000 ft |
| Power Voltage | 100 – 240 VAC, 0.75 – 0.3 A | | |
| Voltage Dynamic Frequency | 47 Hz – 63 Hz | | |
| DIMENSIONS (W x D x H) | | COMPLIANCE | |
| Size Packed | | Arsenic-free Glass | Yes |
| (mm) | 513 x 388 x 124 | PVC-free | Yes |
| (inches) | 20.2" x 15.27" x 4.88" | Mercury-free | Yes |
| Size Unpacked with Stand | | PCC % of Plastic Resins | 85% |
| (mm) | 456 x 188.3 x 372 | EPEAT™ | Silver |
| (inches) | 17.95" x 7.41" x 14.65" | ENERGY STAR® Rating | 6.0 |
| Size Unpacked without Stand (Head Only) | | ULE | No |
| (mm) | 456 x 44.5 x 308 | TCO® | 6.0 |
| (inches) | 17.95" x 1.75" x 12.13" | TCO® Edge | No |
| Distance from Table to Panel (mm / inches) | | TUV | No |
| Lowest Pixel at Bottom of Screen | 90 / 3.54" | RoHS (EU 2002/95/EC) | Yes |
| Highest Pixel at Top of Screen | 354 / 13.94" | Windows Certification | Windows 7, Windows 8, Windows 8.1, Windows 10 |
| Stand Base Footprint Area (mm / inches) | 162.3 x 200.8 / 6.39" x 7.91" | China Energy Efficiency Standard | Tier 1 |
| Weight | | WARRANTY AND AVAILABILITY | |
| Packed | Starting at 8.7 lbs (3.96 kg) | Warranty | 3 Years |
| Unpacked | Starting at 6.2 lbs (2.8 kg) | Geography Availability | World Wide |
| Monitor Head | Starting at 5.4 lbs (2.45 kg) | ThinkVision® Logo | Yes |
| | | Global Model | No |