## ThinkVision T2254p 61BAMAR2US

#### Region

US

Color Raven Black

Panel Twisted Nematic

Display Size 22"

View Area 473.8x296.1 mm

Resolution 1680x1050

Aspect Ratio 16:10

Pixel Pitch 0.282x0.282 mm

Dot / Pixel Per Inch 90 dpi

Brightness 250 nits

Contrast Ratio 1000:1

Pixel Response Time 5 ms

Color Gamut 72%

View Angle (H / V) 170 / 160

Stand Tilt, Swivel, Pivot, Height Adjust Stand

Side Bezel Width 17.1 mm

Dimensions with Stand (HxWxD) 371.7x509.3x242.7 mm

Power Comsuption (Typical / Maximum) 20W / 25W

Power Adapter Integrated

Weight (Including Stand) 10.14lb / 4.60kg

Warranty 3-year ENERGY STAR ENERGY STAR 6.0

TCO TCO 7.0

EPEAT Gold

Presets / User Settings 28 / 20

On Screen Display OSD, 8 Languages

USB Port None

Speaker None

Camera None

Multiple Input VGA, HDMI, DP

Monitor Cable VGA, DP

CPU / Platform None / None

Display Ram / Storage / Card Slot None / None / None

Wireless / Ethernet / Bluetooth None / None / None

Touch Screen / Digitizer Pen / Battery None / None / None

Operating System Support Windows 7, Windows 8, Windows 8.1, Windows 10

Ann Date (mm/yy) 03/15

#### Note:

Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX -Hungary, CY - Cyprus, etc.), and "\*\*" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries



This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area. Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or ftness for a particular purpose.

#### http://psref.lenovo.com

PSREF

Visit psref website for the latest version of Product Specifcations Reference. © Lenovo, 2018. All rights reserved.





### Lenovo ThinkVision T2254p Wide

Product Specifications Reference (PSREF)

Bezel color Type-model Parel	Name	T2254p Wide Flat Panel Monitor	Features
Panel       GOCMAT2EU / 61BAMAT2EU       Supports optional soundiar         Verwahe image size       TF1-LO.D wisde demain (TN), While LED backlight         Native resolutions       16:10         Aspect ratio       0.282 x 0.282 nm         Prese pich (mm)       0.282 x 0.282 nm         Dol/had pi indo       90 dpi         Octor and tail       10:00 (fypical)         Cold gamual       10:00 (fypical)         Cold gamual       72%         Verwahe pointion       20.28 and table spical         Outroat station       10:00 (fypical)         Cold gamual       72%         Verwahe pointion       20.28 and table spical         Outroat spical       72%         Weight       114 58 40 kg         Limited warranty       3 year (inclus backlight)         Astable data       Matresolutabackg         VEAL </td <td>Bezel color</td> <td>Raven black</td> <td></td>	Bezel color	Raven black	
Panel       TFLCD, twisted nematic (TN), While LED backlight       2.00 (569mm) diagonal         Max view area (W x H)       18, 70 'x H 170' (473 Smm x 296.1mm)       3.00 (473 Smm x 296.1mm)         Apped Tailo       0.282 x 0.282 mm       0.282 x 0.282 mm         DoffWal per Inch       90 dpi       0.01 (typical)         Presel pint fm       0.282 x 0.282 mm       0.282 x 0.282 mm         DoffWal per Inch       50 nits or climit (typical)       0.282 x 0.282 mm         Prevent associate time       50 nits or climit (typical)       0.00 (typical)         Viewing angle 10:10: GR 170' (+/- 85') horizontal, 160' (+/- 80') vertical       1.0 entilled         Stage vidit       50 (typical)       50 (typical)         Dimension((thxWDD)       20 watts taindby/suspend, universal,       -0.5 statt standby/suspend, universal,         20 watts taindby/suspend, universal,       -0.6 statt standby/suspend, universal,	Type-model		
Viewide intage size Native resolutions Aspect ratio         22.0° (testimin) diagonal 15:10         - Indides dial input connection for attachment to two systems concurrently (analog and digital)           Aspect ratio         16:10         - EFEAT Gold certified         - Indides dial input connections of attachment to two systems concurrently (analog and digital)           Dar/Frag per Inch Softmas ratio         50 dpi 20 dpi 2	Panel	TFT-LCD, twisted nematic (TN), White LED backlight	Supports ThinkCentre Tiny Clamp Bracket     Supports optional soundbar
Max New Hall (VX F)       16.0       10.0       (V3.26 min X.290, 100)         Pixel pith (mm)       0.282 X 0.282 mm       (Vice)       (Vice)         Definition (mm)       0.282 X 0.282 mm       (Vice)       (Vice)         Period response time       Exercise (Vice)       (Vice)       (Vice)         Colv gamu       72%       (Vice)       (Vice)       (Vice)         Dimension (HxWD)       20 watts tandby/supperd, universal, (Vice)       (Vice)       (Vice)       (Vice)         Dimension (HxWD)       3 year (Includes backlight)       (Vice)       (Vice)       (Vice)       (Vice)         Available date       March 2015       (Vice)       (Vice)       (Vice)       (Vice)       (Vice)         Preset resolutions       V(GA: Edox350, 640:480, 720:400       (Vice)       <			
Aspect ratio       16:10       0.28 x 0.282 mm         Derive pict (min)       0.28 x 0.282 mm       90 dpl         Derive pict (min)       20 dpl       20 mm         Synthesis       20 mm       20 mm         Developing       21 mm       21 mm         Synthesis       77.5%       20 mm         Weing angle at 10:1 CB       170" (+/- 85") horizontal, 160" (+/- 80") vertical       30 mm         Bazet with       20 watts typical,       20 watts typical,       20 watts typical,         20 watts typical,       20 watts typical,       20 watts typical,       20 watts typical,         Veright       10:10 kpl sep mm       20 sep mm       20 contained sep typical,       20 sep sep mm         Veright       10:10 kpl sep mm       20 sep (ncludes backlight)       20 sep sep mm       20 sep sep mm         Veright       10:10 kpl sep mm       20 sep sep mm       20 sep sep mm       20 sep sep mm         Present resolutions       VGA:       128 sep			systems concurrently (analog and digital)
Pikel pitch (mm) 0.282 x 0.282 mm 0.260 rtms traditions 8.1 certified Hitrosoft Windows 7 / Mindows 7 / Mindows 8.1 certified Hitrosoft Windows 8.1 certified Hitrosoft Windows 10 certif			
Durf was       30 dp.       or diff" (typical)         Springs       100 m or diff" (typical)         Power response time       5ms (typical)         Stand       TZ, S.         Vewing angle at 10:1 CB       170" (+/-85") horizontal, 160" (+/-80") vertical         Bazel width       TZ, S.         Stand       TZ, S.         Dimension       14.55" H x 20 of "W. S. ST D:         String of the standby/suspend, universal, it is 4.60 kg       14.55" H x 20 of "W. S. ST D:         String of the standby/suspend, universal, it is 4.60 kg       16.65" STAR" qualified         Power nangent       ENERGY STAR" qualified         Prower nangent       String of TCO Carified Edge 2.0, WEEE, horis, EPAAT" Cold rating         Prower nangent       String	Pixel pitch (mm)		
Contrast ratio Control (typical) Correlation Control (typical) Con			
Pikel response time 5ms (typćal) ' Viewing angle at 10: CB 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel with 50° (+/- 80°) horizontal, 160° (+/- 80°) vertical Bazel warranty - 50° watts standby/suspend, universal, horizontal backlight) - 10. 14 br. 40 kg Bazel warranty - 50° (Class B Environmental - 50° (Class B Environmental - 50° (Class B Environmental - 50° (Class B Environmental - 50° (Class B) Preset resolutions - VGA: 600 kriting WXGA: 1240×781, 1240×781, 1250×768 WXGA: 1240×781, 1260×768 WXGA: 1240×781, 1260×768, 1260×1050 Standard presets (0) 1860×1050 Standard presets (0) 1860×1050 Direct ace diplay with diplatuser controls (6) farguage) Direct ace diplay with diplatuser (Control tors; one PC shows image; select via button) Monifor connectors (1) VGA 15° µn D-shell at each end, analog, 18 meter (3) DisplayPort, diplatuset, MCAP <b>Compliant</b> (3) DisplayPort, diplatuset, MCAP <b>Compliant</b> (3) DisplayPor			
Color gainut 72% Viewing angle to 1:C GR 10 <sup>-</sup> (4- 85 <sup>-</sup> ) horizontal, 160 <sup>o</sup> (4-8 80 <sup>-</sup> ) vertical Tit, swivel, pivot, and height adjustable stand Stade 30 <sup>-</sup> (4-85 <sup>-</sup> ) horizontal, 160 <sup>o</sup> (4-8 80 <sup>-</sup> ) vertical Tit, swivel, pivot, and height adjustable stand Stade 30 <sup>-</sup> (4-85 <sup>-</sup> ) horizontal, 160 <sup>o</sup> (4-8 80 <sup>-</sup> ) vertical Tit, swivel, pivot, and height adjustable stand Stade 30 <sup>-</sup> (4-85 <sup>-</sup> ) horizontal, 160 <sup>o</sup> (4-86 <sup>-</sup> ) vertical Tit, swivel, pivot, and height adjustable stand Stade 30 <sup>-</sup> (4-85 <sup>-</sup> ) valits hytical, integrated (no external brick-like power supply) 10.1 fb : 40.80 kg Limited warranty 3 year (includes backlight) Available data Prover managemet EVENA-compliant Prover managemet EVENA-compliant Prover managemet EVENA-Collass 8 Environmental Environmental Preset resolutions VGA: 640x550, 640x480, 720x400 Standard presets: 28; user settings: US Standard presets: 28; user settings: Direct access (buttos on fron) for automatic image setup, dual input and brightness None Multiple input Multiple			
Stand       Tit, swivel, pivot, and height adjustable stand         Bezel width       Sides: 067* (17: mm H x 505: 067* (17: mm D         Power supply       S1 Arm H x 500: shown W x 24.2: mm D         Power supply       S1 Arm H x 500: shown W x 24.2: mm D         Again and the stand shown W x 24.2: mm D       S1 Arm H x 500: shown W x 24.2: mm D         Yeight       To: 14 b; 4 80 kg         Linited warranty       A year (includes backlight)         Available data       March 2015         VESA-compliant       VESA DDC2BCIC         Power managemet       ENERGY STAR* qualified         Erroironmental       FCC Class B         TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, RoHS, EPEAT** God rating         Preset resolutions       VGA:         Standard presets: 28; user settings:       Standard presets: 28; user settings:         User settings:       Standard presets: 28; user settings:         USB hub       None         Multiple input       March 14, 32* (110mm); swive/ +/-45*; datachable stand         Soreen display with digital user controls (8 languages)       TrinkVision T2254p Wide Monitor         Viewing adjustments       Tit: 30* back, -5* forward: iff: 4.3* (110mm); swive/ +/-45*; datachable stand         Soreen display with digital user controls (8 languages)       TrinkVision T2254p Wide Monitor	Color gamut	72%	
Bazel width Dimensions (HxWz)       Sides: 0.67* (17.1mm)       Start N 2.00* W 3.9.55* D; 371.7mm H x 509.3mm W x 242.7mm D         Power supply       20 watts typical, 25 watts standby/suspend, universal, in f ates tho external brick-like power supply) in f ates tho external brick-like power supply) in f ates abolighth       Image: Comparison of the start of the	Viewing angle at 10:1 CR		
Dimensions (HxWxD) 14.63" H x 20.01" W x 9.55" D; 371.7mm H x 509 smm W x 242.7mm D 20 watts typical, 25 watts standby/suspend, universal, integrated (no external brick-like power supply) Limited warranty 3 year (include sacklight) Available data March 2015 VESA-compliant Preset resolutions VGA: EXTRAT: qualified Environmental TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, RoHS. SEPEAT" Gold rating Preset resolutions VGA: E000 rating Preset resolutions VGA: 1280x768, 1280x800, 1366x768 WXGA: 1024x768, 1152x804 SXGA: 10000 SXGA: 1024x768, 1152x804 SXGA: 100000 SXGA: 1024x768, 1152x804 SXGA: 1000000 SXGA: 10000000 SXGA: 1000000000 SXGA: 1000000000000000000000000000000000000			
Power supply       20 watts typical,         25 watts maximum,       -0.5 watts standby/suspend, universal,         Integrated (no external brick-like power supply)       10.14 bt, 460 kg         Limited waranty       3 yaer (notudes backlight)         Available date       March 2015         VESA-compliant       VESA-compliant         Power management       ENERGY STAR* qualified         Ergonomics       VGC as B         Environmental       TCC Olass B         Environmental       TCC Olass B         Preset resolutions       VGA:       640x400, 720x400         SKGA+:       122x/768, 1220x769, 1220x800, 1366x768       WKGA+:         WSKGA+:       160x900       WSKGA+:       160x900, 1366x768         Wreing adjustments       7///t 30° back, -5° forward; I//t 4.3° (110mm); swivel: +/-45°; detachable stand       Screen pixels 90 degrees from landscape to portrait         Os and presets       Screen pixels 90 degrees from landscape to portrait       Screen pixels 90 degrees from landscape to portrait         Os and presets       State and presets       State and presets       Screen pixels 90 degrees from landscape to portrait         Os and presets       Screen pixels 90 degrees from landscape to portrait       Screen pixels 90 degrees from landscape to portrait         Os and presets       State and Waranty infor		14.63" H x 20.01" W x 9.55" D;	and the second se
25 watts standby/suspend, universal, integrated (no external brick-like power supply) 10,14 b; 460 kg         Hindler dwarnarty       3 year (includes backlight) Available data         Weight       VESA-compliant         Prower management Ergonomics       VESA DC22B/CI Prower management Ergonomics         Preset resolutions       VGA:         Britsion standards       FCC Class B TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, ROHS, EPEAT* Gold rating         Preset resolutions       VGA:         Britsion standards       FCC Class D TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, ROHS, EPEAT* Gold rating         Presets / user settings       Standard presets: 28; user settings: 20         WXGA:       1280x768, 1280x800, 1366x768 WXGA:         WXGA:       1200x768, 1280x800, 1366x768 WXGA:         Viewing adjustments       7///: 30° back, -5° forward; <i>lift</i> : 4.3° (110mm); swirel; +/-45°; detachable stand Soctating Screen Boots 90 degrees from landscape to portrait         On screen display USB hub       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue (2) HDM (14), digital, HDCP-compliant (3) DisplayPort, digital, HD			
-0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) 10.14 lb; 460 kg         User (includes backlight)         VESA-compliant         VESA-compliant         VESA-compliant         Tess ADDC2R/CI Power management         Environmental         TCC Displays 7.0, TCO Certified Edge 2.0, WEEE, RoHS, EPEAT** Gold rating         Preset resolutions       VGA: KGA:         VGA:       E40x305, 640x480, 720x400 SGA:         VGA:       120x4768, 1122x864 SKGA:         SKGA:       1120x768, 1220x800, 1366x768 WXGA:         Viewing adjustments Rotein pixels settings: 20       Standard presets: 28; WKGA:         Viewing adjustments Conscreen display       Tilt: 30° back, 5° forward; lift: 4.3° (110mm); swivel: +/-45°; detachable stand Screen pixels 90 degrees from landscape to portrait On screen display with digital user controls (6 languages) Defendences bickutons on from ly for automatic image setup, dual input and brightness Defendences bickutons on from ly for automatic image setup, dual input and brightness Defendences bickutons on from ly for automatic image setup, dual input and brightness Defendences bickutons on from ly for automatic image setup, dual input and brightness Defendences bickutons on from ly for automatic image setup, dual input and brightness Defendences bickutons on from ly for automatic image setup, dual input and brightness Defendences bickutons on from ly for automatic image setup, dual input and brightness Defendences bickutons on from ly for automatic image setup, dual input and brightness Defendences bickutons on from ly for automatic image setup	Power supply		and the second se
weight Limited waranty       10.14 bit ;4.80 kg 3 year (includes backlight)         Available data wailable data waranty       3 year (includes backlight)         Available data Power management Ergonomics       VESA DOC2B/CI SO 9241-307         Present standards       FCC class B TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, ROHS, EPEAT <sup>W</sup> Gold rating         Preset resolutions       VGA:       640x350, 640x400, 720x400 XGA:       1024x768, 1152x864 SKGA:         SKGA:       1220x1024 WXKGA:       1200x1024 WXKGA:       1020x400, 1366x768 WXSGA:       1020x1024 WXKGA:         Presets / user settings       70f: 30° back, -5° forward; <i>lif:</i> 4.3° (110mm); swivel: +/-45°; detachable stand Screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup, dual input and brightness None       None         Multiple input Monitor connectors       T01: 30° back, -5° forward; <i>lif:</i> 4.3° (110cmm); swivel: +/-45°; detachable stand Screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup, dual input and brightness None         Multiple input Monitor connectors       T01: 30° back, -5° forward; <i>lif:</i> 4.3° (110cmm); swivel: +/-45°; detachable stand Screen display with digital detach the date and end, alage, 1.8 meter         (2) HDMI (1-4), digital, HDCP-compliant (3) DisplayPort in each end, analog, 1.8 meter         (3) DisplayPort indigital, HBCP HCP-compliant (3) detachable, VGA 15- pin D-shell analog, blue (2) HDMI (1-4), digital, HDCP-compliant (3) detachable, DisplayPort in each end, digita			and the second se
Limifed warranty Available data March 2015 VESA-compliant VESA DDC2B/CI ENERGY STRAP qualified Ergenomics FCC Class B Environmental FCC Class B FCC Class B Environmental FCC Class B FCC FTCC Class B FCC Class B FCC Class B FCC Class B FCC FTC FTC FTCC FTCC FTCC FTCC FTCC FT		integrated (no external brick-like power supply)	and the second
Available date       March 2015       March 2015         VESA-compliant       VESA DDC2B/CI         Prower management       RENERGY STAR* qualified         Ernssion standards       ECC Class B         Environmental       CC Class B         Preset resolutions       VGA:       640x450, 640x480, 720x400         XGA:       1280x1624         WXGA:       1024x768, 1152x864         SXGA:       1280x1624         WXGA:       1280x768, 1280x800, 1366x768         WXGA:       1280x768, 1280x800, 1366x768         WXGA:       1280x768, 1280x800, 1580x1050         Standard presest: 28; user settings       User settings         On screen display with digital user controls (6 languages)       Direct access (buttons on front) for automatic image setup, dual input and brightness         None       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)         Monitor connectors       (1) 40a disal, MDCP-compliant         Signal cables       (2) HOM (1.4), digital, MDCP-compliant         Signal cables       (2) etabathe, Kow converted of attach to the part analog, blue         (2) HOM (1.4), digital, MDCP-compliant       10 beak-compliant         Security Security Keylole for attachment of optional cable lock (Kensington* lock-compatible)       Sceurity Security keylole fo			And the second
VESA-compliant Power management Ergonomics       VESA DDC2B/CI ENERGY STAR* qualified Enversion standards         Enversion standards       ENERGY STAR* qualified Enversion standards         Environmental       TGC Displays 7.0, TCO Certified Edge 2.0, WEEE, RoHS, EPEAT*** Gold rating         Preset resolutions       VGA:       600x480, 720x400 SVGA:       600x480, 720x400 SVGA:         VGA:       120x1024       WXGA:       120x1024         WXGA:       120x1768, 1220x600, 1366x768 WXGA+:       140x900 WSCA+:       160x900, 1860x150         Presets / user settings       Standard presets: 28; user settings: 20			
Power management Engenomics Ergonomics Ervironmental FroC Class B Ervironmental FroC Class B Ervironmental FroC Class B Ervironmental FroC Class B FroC Class B FroM FroM FroM Class Class B FroM FroM FroM Class Class B FroM FroM FroM Class Class B FroM FroM FroM FroM FroM FroM FroM FroM			
Ergonomics       ISO 9241-307         Emission standards Environmental       FoC C class B TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, RoHS, EPEAT*** Gold rating         Preset resolutions       VGA:       640x350, 640x480, 720x400 SVGA:       152x864 SXGA:       1280x1024         WKGA:       1280x788, 1280x800, 1366x768 WKGA::       1280x788, 1280x800, 1366x768 WKGA::       1280x802         Presets / user settings       Standard presets: 28; user settings:       Till: 30° back, -5° forward; <i>lift</i> : 4.3° (110mm); <i>swivel:</i> +/-45°; detachable stand Scareen display       Till: 30° back, -5° forward; <i>lift</i> : 4.3° (110mm); <i>swivel:</i> +/-45°; detachable stand Scareen display         On screen display       On screen display with digital user controls (8 languages)       On screen display On screen display with digital user controls (8 languages)         UBI input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue       2) HDMI (14), digital, MDC-P-compliant (3) DisplayPort, digital, black, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (3			
Emission standards Environmental       FCC Class B TCO Displays 7.0, TCO Certified Edge 2.0, WEEE, RoHS, EPEAT™ Gold rating         Preset resolutions       VGA: 640x350, 640x480, 720x400 XGA: 1024x788, 1152x864 XXGA: 1280x1024 WXGAA: 140x900 WSXGAA: 1600x900, 1680x1050         Presets / user settings       Standard presets: 28; user settings: 20         Viewing adjustments Rotating screen On screen display Conscreen display Conscreen display with digital user controls (8 languages) Control features US8 hub None       Tilt: 30° back, -5° forward; <i>lift:</i> 4.3° (110mm); <i>swivel:</i> +/-45°; detachable stand Screen pivots 90 degrees from landscape to portrait On screen display with digital user controls (8 languages) Control features US8 hub None       Tilt: 30° back, -5° forward; <i>lift:</i> 4.3° (110mm); <i>swivel:</i> +/-45°; detachable stand Screen pivots 90 degrees from landscape to portrait On screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup, dual input and brightness None         Multiple input Multiple input Monitor connectors       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) WGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, UsplayPort at each end, digital, 1.8 meter (2) detachable, DisplayPort, digital, black, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (4) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (3) detachable, DisplayPort, at each end, digital, 1.8 meter (4) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (5) detachable, DisplayPort, en	Ergonomics		
RoHS, EPEATM Gold rating         Preset resolutions       VGA: SVGA: SVGA: 200x500       640x350, 640x480, 720x400         SVGA: XGA: SVGA: WXGA: 1280x7024       152x864       State WXGA: WXGA: 1280x7024       152x864         Presets / user settings       Standard presets: Standard presets: 28; user settings: 20       ThinkVision T2254p Wide Monitor         Viewing adjustments Rotating screen On screen display Control features       Till: 30° back, -5° forward; <i>lift:</i> 4.3° (110mm); <i>swivel:</i> +/-45°; detachable stand Screen pivots 90 degrees from landscape to portrait On screen display with digital user controls (8 languages) Control features       Direct access (buttons on front) for automatic image setup, dual input and brightness None       None         Multiple input       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) WGA 15-pin D-shell analog, blue       None         Multiple input       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (2) HDMI (14), digital, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (3) DisplayPort, digital, analog, atteach at each end, analog, 1.8 meter (2) detachable, JSA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, JSA 15-pin D-shell at each end, atteach end, atteach end, atteach end, atteach end, atteach end (3) DisplayPort, envery and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter black power cord       Accessories <td></td> <td></td> <td></td>			
Preset resolutions       VGA:       640x350, 640x480, 720x400         SVGA:       800x600         XGA:       1024x768, 1152x864         SXGA:       1280x768, 1220x800, 1366x768         WXGA:       1280x768, 1220x800, 1366x768         WXGA:       1440x900         WSXGA:       1400x900         WSXGA:       1280x768, 1220x800, 1366x768         WXGA:       1280x761, 1400x900         WSXGA:       1280x761, 1400x900         WSXGA:       1280x762, 283         user settings:       Standard presets: 28;         user settings:       On screen display         On screen display       On screen display with digital user controls (6 languages)         Control features       Direct access (buttons on front) for automatic image setup, dual input and brightness         None       None         Multiple input       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)         Monitor connectors       (1) VGA 15-pin D-shell, analog, blue         Bipalpevort, digital, HDCP-compliant       (3) DisplayPort, digital, AlbCP-compliant         Gignal cables       (1) detachable, NGA 15-pin D-shell at each end, analog, 1.8 meter         (2) detachable, DisplayPort at each end, digital, 1.8 meter       (2) detachable, NGA 15-pin D-shell at each end, digit	Environmental		lenovo
SVGA:       600×600 XGA:       1024x768, 1152x864 SXGA:       1280x1024 WXGA:       1280x1024 WXGA:       1280x768, 1220x800, 1366x768 WXGA:       1280x768, 1220x800, 1366x768 WXGA:       1280x768, 1280x800, 1366x768 WXGA:       1400x900 WSXGA:       1600x900, 1680x1050         Presets / user settings       Standard presets:       28; user settings:       Till: 30° back, -5° forward; <i>lift:</i> 4.3° (110mm); <i>swivel:</i> +/-45°; detachable stand Screen pivots 90 degrees from landscape to portrait On screen display with digital user controls (6 languages) Direct access (buttons on fron) for automatic image setup, dual input and brightness None USB hub None       Direct access (buttons on fron) for automatic image setup, dual input and brightness None         USB hub Multiple input Monitor connectors       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shelli, analog, blue (2) HDMI (1-4), digital, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (3) detachable, VGA 15-pin D-shelli at each end, analog, 1.8 meter (2) detachable, VGA 15-pin D-shelli at each end, analog, 1.8 meter (2) detachable, VGA 15-pin D-shelli at each end, digital, 1.8 meter (2) detachable, VGA 15-pin D-shelli at each end, digital, 1.8 meter (3) detachable, VGA 15-pin D-shelli at each end, digital, 1.8 meter (3) detachable, VGA 15-pin D-shelli at each end, digital, 1.8 meter (3) detachable, VGA 15-pin D-shelli at each end, digital, 1.8 meter (3) detachable, VGA 15-pin D-shelli at each end, digital, 1.8 meter (3) detachable, VGA 15-pin D-shelli at each end, digital, 1.8 meter (3) detachable, VGA 15-pin D-shelli at each end, digital, 1.8 meter (3) detachable, VGA 15-pin D-shelli at each end, digital, 1.8 meter (3) detachable, DisplayPort detacharent of optiona	Dreast resolutions		
XGA:       1024x768, 1152x864 WXGA:       1280x1024 WXGA:       1280x768, 1280x800, 1366x768 WXGA:       1280x768, 1280x800, 1366x768 WXGA:       1440x900         Presets / user settings       Standard presets: 28; user settings 2.0       ThinkVision T2254p Wide Monitor         Viewing adjustments       7///: 30° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; detachable stand Screen pivots 90 degrees from landscape to portrait On screen display       Thit: 30° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; detachable stand Screen pivots 90 degrees from landscape to portrait On screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup, dual input and brightness None         USB hub       Direct access (buttons on front) for automatic image setup, dual input and brightness         Multiple input       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue         Signal cables       (1) detachable, VGA 15-pin D-shell analog, blue (2) etachable, DisplayPort at each end, analog, 1.8 meter         Signal cables       (2) detachable, DisplayPort at each end, analog, 1.8 meter         Gounting features       Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount Security Wyhole for attachment of optional cable lock (Kensington* lock-compatible)         Ship group       Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter black power cord       Accessories      <	Preset resolutions		
SXGA:       1280x768, 1280x768, 1280x800, 1366x768         WXGA:       1280x768, 1280x800, 1366x768         WXGA:       1400x900         WSXGA:       1600x900, 1680x1050         Standard presets:       22;         user settings:       20         Viewing adjustments       7/lf:         Rotating screen       Screen pivots 90 degrees from landscape to portrait         On screen display       On screen display         On screen display       Direct access (buttons on front) for automatic image setup, dual input and brightness         USB hub       None         Multiple input       Mone         Ula lipput (two different PCs attach to two different connectors; one PC shows image; select via button)         (1) VGA 15-pin D-shell, analog, blue         Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount         Signal cables       (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter         (2) HDM (1/l, d), digital, black, HDCP-compliant         (3) DisplayPort, digital, black, HDCP-compliant         (3) DisplayPort at each end, digital, 1.8 meter         (2) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter         (2) detachable, VGA 15-pin D-shell at each end, digital, 1.8 meter         (2) detachable, OFA 15-pin D-shell at each end, digital, 1.8 meter			
Presets / user settings       WXGA+: 140x900 WXSXGA+: 1600x900, 1680x1050 Standard presets: 28; user settings: 20         Viewing adjustments Rotating screen On screen display On screen display Direct access (buttons on front) for automatic image setup, dual input and brightness None USB hub Multiple input (1) VGA 15-pin D-shell, analog, blue (2) HDMI (14), digital, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (3) DisplayPort at each end, digital, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter (2) detachable, UGA 15-pin D-shell at each end, digital, 1.8 meter (2) detachable, UGA 15-pin D-shell at each end, digital, 1.8 meter (2) detachable, UGA 15-pin D-shell at each end, digital, 1.8 meter (3) DisplayPort at each end, digital, 1.8 meter (3) DisplayPort distant distant of optional cable lock (Kensington® lock-compatible) Ship group Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter black power cord Limited Warranty See details at http://support.lenovo.com/en_US/guides-and-manuals/de- tail.page?DocID=UM008281       Accessories Kensington Twin Head Cable Lock 45K1620		SXGA: 1280x1024	
Presets / user settings       WSXGA+: 1600x900, 1680x1050 Standard presets: 28; user settings: 20       ThinkVision T2254p Wide Monitor         Viewing adjustments Rotating screen On screen display On screen display USB hub Multiple input       Tilt: 30° back, -5° forward; <i>lift:</i> 4.3° (110mm); <i>swivel:</i> +/-45°; detachable stand Screen privots 90 degrees from landscape to portrait On screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup, dual input and brightness None USB hub Monitor connectors       None Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell analog, blue (2) HDM (1.4), digital, HDCP-compliant (3) DisplayPort, digital, black, HDCP-compliant (2) detachable, DisplayPort at each end, digital, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount Security         Security       Security keyhole for attachment of optional cable look (Kensington* lock-compatible)         Ship group       Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter black power cord         See details at http://support.lenovo.com/en_US/guides-and-manuals/de- tail.page?DocID=UM008281       Accessories         See details at www.lenovo.com/support/monitoraccessc       See details at www.lenovo.com/support/monitoraccessc		WXGA: 1280x768, 1280x800, 1366x768	
Presets / user settings       Standard presets: 28; user settings: 20       ThinkVision T2254p Wide Monitor         Viewing adjustments Rotating screen       Till: 30° back, -5° forward; lift: 4.3" (110mm); swivel: +l-45°; detachable stand Screen pivots 90 degrees from landscape to portrait On screen display Control features       Screen pivots 90 degrees from landscape to portrait On screen display with digital user controls (8 languages)         USB hub       Direct access (buttons on front) for automatic image setup, dual input and brightness None       Direct access (buttons on front) for automatic image setup, dual input and brightness None         Multiple input Monitor connectors       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue (2) HDMI (1.4), digital, HDCP-compliant (3) DisplayPort, digital, HDCP-compliant (3) DisplayPort, digital, HDCP-compliant (3) DisplayPort, digital, HDCP-compliant (3) DisplayPort at each end, alalog, 1.8 meter (2) detachable, USA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, VGA 15-pin D-shell at each end, digital, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter (3) DisplayPort.lenovo.com/en_US/guides-and-manuals/de- tail.page?DocID=UM008281       Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter black power cord         Limited Warranty       Accessories         See details at http://support.lenovo.com/en_US/guides-and-manuals/de- tail.page?DocID=UM008281       See details at www.lenovo.com/support/monitoraccessoci/sisite at www.lenovo.com/support/monitoraccessoci/sisite		WSXGA+: 1440X900 WSXGA+: 1600x900 1680x1050	
Viewing adjustments       Tilt: 30° back, -5° forward; lift: 4.3" (110mm); swivel: +1/-45°; detachable stand         Rotating screen       Screen pivots 90 degrees from landscape to portrait         On screen display       On screen display with digital user controls (8 languages)         Control features       Direct access (buttons on front) for automatic image setup, dual input and brightness         Wontior connectors       None         Multiple input       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)         Monitor connectors       (1) VGA 15-pin D-shell, analog, blue         (2) HDMI (1.4), digital, HDCP-compliant       (3) DisplayPort, digital, hBCA, HDCP-compliant         (3) DisplayPort, digital, black, HDCP-compliant       (3) DisplayPort at each end, analog, 1.8 meter         (2) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter       (2) detachable, DisplayPort at each end, digital, 1.8 meter         Mounting features       Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount         Security       Security keyhole for attachment of optional cable lock (Kensington* lock-compatible)         Ship group       Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter DP signal cable, 1.8 meter black power cord         See details at http://support.lenovo.com/en_US/guides-and-manuals/de-tail.page?DocID=UM008281       See details at www.lenovo.com/s	Presets / user settings	Standard presets: 28:	ThinkVision T2254n Wide Monitor
Rotating screen       Screen pivots 90 degrees from landscape to portrait         On screen display       On screen display with digital user controls (8 languages)         Control features       Direct access (buttons on front) for automatic image setup, dual input and brightness         Wultiple input       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)         Multiple input       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)         Monitor connectors       (1) VGA 15-pin D-shell, analog, blue         (2) HDM (1.4), digital, black, HDCP-compliant       (3) DisplayPort, digital, black, HDCP-compliant         Signal cables       (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter         Mounting features       Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount         Security keyhole for attachment of optional cable lock (Kensington" lock-compatible)         Ship group       Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, at http://support.lenovo.com/en_US/guides-and-manuals/de-         Kensington MicroSaver Cable Lock       73P2582         Kensington Twin Head Cable Lock       45K1620         See details at http://support/monitoraccessori       See details at www.lenovo.com/support/monitoracces		user settings: 20	
Rotating screen       Screen pivots 90 degrees from landscape to portrait         On screen display       On screen display with digital user controls (8 languages)         Control features       Direct access (buttons on front) for automatic image setup, dual input and brightness         Wultiple input       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)         Multiple input       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)         Monitor connectors       (1) VGA 15-pin D-shell, analog, blue         (2) HDM (1.4), digital, HDCP-compliant       (3) DisplayPort, digital, black, HDCP-compliant         Signal cables       (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter         (2) detachable, DisplayPort at each end, digital, 1.8 meter       (2) detachable, DisplayPort at each end, digital, 1.8 meter         Mounting features       Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount         Security keyhole for attachment of optional cable lock (Kensington* lock-compatible)       Ship group         Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter Dlack power cord       Accessories         Kensington MicroSaver Cable Lock       73P2582         Kensington MicroSaver Cable Lock       45K1620         See details at http://support/monitoraccessori <td< td=""><td></td><td></td><td></td></td<>			
On screen display Control features       On screen display with digital user controls (8 languages)         Direct access (buttons on front) for automatic image setup, dual input and brightness None       Direct access (buttons on front) for automatic image setup, dual input and brightness         Multiple input       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)         Monitor connectors       (1) VGA 15-pin D-shell, analog, blue         (2) HDM (1.4), digital, HDCP-compliant       (3) DisplayPort, digital, black, HDCP-compliant         (3) DisplayPort, digital, black, HDCP-compliant       (3) DisplayPort at each end, digital, 1.8 meter         Mounting features       Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount         Security       Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)         Ship group       Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.9 meter Black power cord         Kensington MicroSaver Cable Lock 73P2582         See details at http://support.lenovo.com/en_US/guides-and-manuals/details at www.lenovo.com/support/monitoraccessories         See details at www.lenovo.com/support/monitoraccessories		<i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/	-45°; detachable stand
Control features Direct access (búttons on front) for automatic image setup, dual input and brightness USB hub None Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Monitor connectors (1) VGA 15-pin D-shell, analog, blue (2) HDMI (1.4), digital, HDCP-compliant Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter Mounting features Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible) Ship group Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter black power cord Limited Warranty Security See details at http://support.lenovo.com/en_US/guides-and-manuals/de- tail.page?DocID=UM008281 Security Monitor accessories at www.lenovo.com/support/monitoraccessor			(201
USB hub       None         Multiple input       Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)         Monitor connectors       (1) VGA 15-pin D-shell, analog, blue         (2) HDMI (1.4), digital, HDCP-compliant       (3) DisplayPort, digital, black, HDCP-compliant         (3) DisplayPort, digital, black, HDCP-compliant       (3) DisplayPort, digital, black, HDCP-compliant         (4) VGA 15-pin D-shell at each end, digital, 1.8 meter       (2) detachable, DisplayPort at each end, digital, 1.8 meter         Mounting features       Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount         Security       Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)         Ship group       Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 2.8 meter DP signal cable, 3.8 meter DP signal cable, 4.8 meter DP signal cable, 2.8 meter DP signal cable, 4.8 meter DP signal cable, 4.8 meter DP			
Monitor connectors       (1) VGÅ 15-pin D-shell, analog, blue         (2) HDMI (1.4), digital, HDCP-compliant         (3) DisplayPort, digital, black, HDCP-compliant         Signal cables       (1) detachable, VGÅ 15-pin D-shell at each end, analog, 1.8 meter         Mounting features       Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount         Security       Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)         Ship group       Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter Context, 1.8 meter Signal Cable Deck         See details at http://support.lenovo.com/en_US/guides-and-manuals/de-tail.page?DocID=UM008281       See details at www.lenovo.com/support/monitoraccessor         See details at www.lenovo.com/support/monitoraccessor       See details at www.lenovo.com/support/monitoraccessor		None	
<ul> <li>(2) HDMI (1.4), digital, HDCP-compliant</li> <li>(3) DisplayPort, digital, black, HDCP-compliant</li> <li>(1) detachable, VGA 15-pin D-shell at each end, digital, 1.8 meter</li> <li>Mounting features</li> <li>Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount</li> <li>Security</li> <li>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</li> <li>Ship group</li> <li>Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter DP signal cable, 1.8 meter black power cord</li> <li>Limited Warranty</li> <li>See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</li> <li>Kensington MicroSaver Cable Lock 73P2582</li> <li>Kensington Twin Head Cable Lock 45K1620</li> <li>See details at www.lenovo.com/support/monitoraccesso</li> </ul>			nnectors; one PC shows image; select via button)
(3) DisplayPort, digital, black, HDCP-compliant         Signal cables       (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter         Mounting features       Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount         Security       Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)         Ship group       Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter black power cord         Limited Warranty       Accessories         See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281       Kensington MicroSaver Cable Lock 73P2582         Kensington Twin Head Cable Lock       73P2582         See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281       See details at www.lenovo.com/support/monitoraccesso	MONITOR CONNECTORS		
(2) detachable, DisplayPort at each end, digital, 1.8 meter         Mounting features       Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount         Security       Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)         Ship group       Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter black power cord         Limited Warranty       Accessories         See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281       Kensington MicroSaver Cable Lock 73P2582         Kensington Twin Head Cable Lock       45K1620         See details at www.lenovo.com/support/monitoraccessor		(3) DisplayPort, digital, black, HDCP-compliant	
Mounting features Security         Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)           Ship group         Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter black power cord           Limited Warranty         Accessories           See details at http://support.lenovo.com/en_US/guides-and-manuals/de- tail.page?DocID=UM008281         Kensington MicroSaver Cable Lock 73P2582           Kensington Twin Head Cable Lock         45K1620           See details at www.lenovo.com/support/monitoraccessor	Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analo	g, 1.8 meter
Security         Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)           Ship group         Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DP signal cable, 1.8 meter black power cord           Limited Warranty         Accessories           See details at http://support.lenovo.com/en_US/guides-and-manuals/de-tail.page?DocID=UM008281         Kensington MicroSaver Cable Lock 73P2582           Kensington Twin Head Cable Lock         45K1620           See details at www.lenovo.com/support/monitoraccesso	Mounting features	(2) detachable, DisplayPort at each end, digital, 1.8 m Wall or desk mounting using the Extend Arm or third-r	eler party accessories, 100mm x 100mm mount
Limited Warranty       Accessories         See details at http://support.lenovo.com/en_US/guides-and-manuals/de- tail.page?DocID=UM008281       Kensington MicroSaver Cable Lock 73P2582 Kensington Twin Head Cable Lock 45K1620         See details at www.lenovo.com/support/monitoraccessor		Security keyhole for attachment of optional cable lock	(Kensington® lock-compatible)
Limited Warranty See details at http://support.lenovo.com/en_US/guides-and-manuals/de- tail.page?DocID=UM008281 Accessories Kensington MicroSaver Cable Lock 73P2582 Kensington Twin Head Cable Lock 45K1620 See details at www.lenovo.com/support/monitoraccessor	Ship group		1.8 meter analog signal cable, 1.8 meter DP signal cable,
See details at http://support.lenovo.com/en_US/guides-and-manuals/de- tail.page?DocID=UM008281       Kensington MicroSaver Cable Lock 73P2582         Kensington Twin Head Cable Lock       45K1620         See details at www.lenovo.com/support/monitoraccesso		· · · · · · · · · · · · · · · · · · ·	
tail.page?DocID=UM008281       Kensington MicroSaver Cable Lock 73P2582         Kensington Twin Head Cable Lock 45K1620         See details at www.lenovo.com/support/monitoraccessor		•	Accessories
Kensington Twin Head Cable Lock       45K1620         See details at www.lenovo.com/support/monitoraccesso			Kanaington MigroPower Ochle Lock
See details at www.lenovo.com/support/monitoraccesso	tail.page?DocID=UM00	0201	
			See details at www.lenovo.com/support/monitoraccessories
See all monitors at www.lenovo.com/thinkvision			
			See all monitors at www.lenovo.com/thinkvision
			Lenovo November 2016

November 2016

# ThinkVision T2254p













