

Philips

LED-backlit LCD monitor

- E-line
- 22 (Viewable 21.5"/54.6 cm) Full HD (1920 x 1080)

227E6QDSW/00

Vivid colours, crisp details

in an elegant design

This brilliant IPS-ADS display offers stunning visuals wrapped in an elegance-inspired design for a light and fresh face in any home or office.

Benefits

Superb Picture Quality

- IPS-ADS wide-view technology for image and colour accuracy
- 16:9 Full HD display for crisp, detailed images
- TrueVision ensures lab quality images
- SmartImage Lite for easy optimised image settings
- SmartControl Lite: For quick and easy display tuning
- SmartContrast for deep black level details

Elegant Design

- Modern Touch controls complement the design
- Elegant, slim design complements your home decor
- Superb glossy finish enhances your home decoration

Experience immersive multimedia

- MHL technology for enjoying mobile content on a big screen
- HDMI-ready for Full HD entertainment



Features

IPS-ADS technology



IPS-ADS displays use an advanced technology that gives you extra-wide viewing angles of 178/178 degrees, making it possible to view the display from almost any angle. Unlike standard TN panels, IPS-ADS displays give you remarkably crisp images with vivid colours, making them ideal not only for Photos, movies and web browsing, but also for professional applications that demand colour accuracy and consistent brightness at all times.

16:9 Full HD display



The Full HD screen has the widescreen resolution of 1920 x 1080p. This is the highest resolution of HD sources for the best possible picture quality. It is fully future-proof as it supports 1080p signals from all sources, including the most recent sources such as Blu-ray and advanced HD game consoles. The signal processing is extensively upgraded to support this much higher signal quality and resolution. It produces brilliant flicker-free progressive scan pictures with superb brightness and colours.

TrueVision





TrueVision is a proprietary Philips technology that uses an advanced algorithm for testing and aligning monitor display, which gives you the ultimate display performance. Philips ensures that TrueVision monitors leave the factory fine-tuned with this process giving you consistent colour and picture quality.

SmartImage Lite

SmartImage Lite is an exclusive, leading edge Philips technology that analyses the content displayed on your screen. Based on a scenario you select, SmartImage Lite dynamically enhances the contrast, colour saturation and sharpness of images and videos for ultimate display performance - all in real time with the press of a single button.

SmartControl Lite

SmartControl Lite is the next generation 3D icon-based GUI monitor control software. This allows the user to fine-tune most parameters of the monitor like Colour, Brightness, screen calibration, Multimedia, ID management etc with the mouse.

SmartContrast



SmartContrast is a Philips technology that analyses the contents you are displaying, automatically adjusting colours and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

Modern Touch controls



Touch control

Touch controls are intelligent, touch-sensitive icons that replace protruding buttons to allow users to adjust the monitor to their requirements. Responding to the lightest touch, Touch control gives the monitor a modern feel.

MHL technology



Mobile High-Definition Link (MHL) is a mobile audio/video interface for directly connecting mobile phones and other portable devices to high-definition displays. An optional MHL cable allows you to simply connect your MHL-capable mobile device to this large Philips MHL display and watch your HD videos come to life with full digital sound. Now not only can you enjoy your mobile games, photos, movies or other apps on its big screen, you can simultaneously charge your mobile device so you never run out of power halfway.

Specifications

Please note that this is a pre-sales leaflet. The contents of this leaflet reflect the best of our knowledge per date and country mentioned above. The contents of this leaflet are subject to change without notice. Philips does not accept any liability as to the contents of this leaflet.

Picture/Display

LCD panel type IPS-ADS LCD
Backlight type W-LED system
Panel Size 21.5 inch/54.6 cm
Effective viewing area Aspect ratio 16:9
Optimum resolution 1920 x 1080 @ 60 Hz

Response time (typical)

SmartResponse (typical)

:Response 5 ms (Grey to Grey)

(typical) Brightness

Brightness 250 cd/ Contrast ratio 1000:1

(typical)

 SmartContrast
 20,000,000:1

 Pixel pitch
 0.248 x 0.248 mm

 Viewing angle
 178° (H)/178° (V)

 @ C/R > 10

Picture enhancement

250 cd/m² 1000:1 20,000,000:1 0.248 x 0.248 mm

Smartlmage Lite

Display colours 16.7 M

Scanning Frequency 30–83 kHz (H)/56–75 Hz (V)

sRGB Yes

MHL 1080p@30Hz

Connectivity

Signal Input VGA (Analogue)
DVI-D (digital, HDCP)
MHL-HDMI (digital, HDCP)

Sync Input Separate Sync
Sync on Green

Audio (In/Out) HDMI audio out

Convenience

User convenience

Power On/Off Menu 4:3/Wide Input OSD Languages

SmartImage lite Brazil Portuguese

Czech Dutch English Finnish French

Hungarian Portuguese

Simplified Chinese

Traditional Chinese

Ukrainian Kensington lock DDC/ČI Mac OS X sRGB

Other convenience Plug and Play Compatibility

Stand

Tilt

Power

On mode 15.52 W (typ.) (EnergyStar 6.0 test

0.5 W (typ.) Standby mode 0.3 W (typ.) Power LED indicator Operation - White

Power supply

Dimensions

Off mode

Product with stand

(mm)

stand (mm)

Packaging in mm (W

 $\times H \times D$

German Greek

Italian Japanese Korean Polish

Russian

Spanish Swedish

Turkish

Windows 7 Windows 8

-5/20 degree

method)

Standby mode - White (flashing)

External

100-240 VAC, 50-60 Hz

511 x 400 x 212 mm

Product without 511 x 318 x 36 mm

562 x 466 x 106 mm

Weight

Product with stand 2.95 kg

(kg)

Product without 2.58 kg

stand (kg)

Product with pack-4.50 kg

aging (kg)

Operating conditions

Temperature range (operation)

Temperature range

(storage)

Relative humidity 20-80% % Altitude

Operation: +12,000 ft (3658 m), Non-

operation: +40,000 ft (12,192 m)

MTBF 30,000 hour(s)

Sustainability

Environmental and

energy

EnergyStar 6.0 EPEAT Silver RoHS Lead-free Mercury Free

100 %

0°C to 40°C °C

-20°C to 60°C °C

Recyclable packaging

material

Compliance and standards

Regulatory Approvals **BSMI**

CE Mark cETLus FCC Class B GOST PSB SASO SEMKO TCO 6.0

TUV/ISO9241-307

WEEE

Cabinet

White Colour Finish Glossy

^{*} Smart response time is the optimum value from either GtG or GtG (BW) tests.



data subject to change 2014, December 18

Version: 3.0.1 EAN: 8712581709570 © 2014 Koninklijke Philips Electronics N.V.

All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

^{*} This Philips display is MHL-certified. However, if your MHL device does not connect or work correctly, check with your MHL device FAQ or vendor directly for instructions. The policy of your device manufacturer may require you to purchase its brand-specific MHL cable or adapter in order for it to work

^{*} Requires optional MHL-certified mobile device and MHL cable (not included). Please check with your MHL device vendor for compatibility.

^{*} Standby/Off energy saving of ErP is not applicable for the MHL charging functionality

^{* &}quot;IPS" word mark / trademark and related patents on technologies belong to their respective owners.