

LCD monitor with SmartImage lite

- Ultra-Narrow Bezel
- 27" (68.6 cm) MHL

274E5OHAW/01

Vibrant images with AH-IPS display

with Ultra-Narrow Bezel, MHL

This attractive Philips display with ultra-narrow bezel and AH-IPS screen gives you awesome, vibrant colour images. Mobile HD link allows you to mirror your Smartphone.

Benefits

Entertainment with Mobile HD Link (MHL)

- MHL technology for enjoying mobile content on a big screen
- Superb 12 watts stereo sound
- HDMI-ready for Full HD entertainment
- · Charge your mobile device while watching a movie
- Optional MHL cable allows for HD video audio playback

Awesome picture quality

- · AH-IPS display gives awesome images with wide viewing angles
- SmartImage Lite for an enhanced LCD viewing experience

- 16:9 Full HD display for crisp, detailed images
- TrueVision ensures lab quality images

Stylish design

- Minimalistic looks with Ultra-Narrow Bezel
- · Superb glossy and textured finish
- VESA mount for convenience



Features

MHL technology



Mobile High-Definition Link (MHL) is a mobile audio/video interface for directly connecting mobile phones and other portable devices to high-definition displays. An optional MHL cable allows you to simply connect your MHL-capable mobile device to this large Philips MHL display and watch your HD videos come to life with full digital sound. Now not only can you enjoy your mobile games, photos, movies or other apps on its big screen, you can simultaneously charge your mobile device so you never run out of power halfway.

AH-IPS technology



AH-IPS displays use an advanced technology that gives you extra-wide viewing angles of 178/178 degrees, making it possible to view the display from almost any angle. Unlike standard TN panels, AH-IPS displays give you remarkably crisp images with vivid colours, making them ideal not only for Photos, movies and web browsing, but also for professional applications that demand colour accuracy and consistent brightness at all times.

Ultra-Narrow Bezel

Utilising the latest technology panels, the new Philips displays are designed with a minimalistic approach by limiting the outer bezel thickness to about 2.5 mm. Combined with an in-panel black matrix strip of around 9 mm, the overall bezel dimensions are reduced significantly, minimising distractions and maximising viewing size. Especially suited to multi-display or tiling setups like gaming, graphics design and professional applications, the Ultra-narrow bezel display gives you the feeling of using one large display.

SmartImage Lite

SmartImage Lite is an exclusive, leading edge Philips technology that analyses the content displayed on your screen. Based on a scenario you select, SmartImage Lite dynamically enhances the contrast, colour saturation and

sharpness of images and videos for ultimate display performance - all in real time with the press of a single button.

Superb 12 watts stereo sound

A pair of high-quality stereo speakers built into a display device. They may be visible front firing, or invisible down firing, top firing, rear firing etc. depending on model and design.

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. An HDMI cable enables high-quality digital video and audio to be transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

16:9 Full HD display



Picture quality matters. Regular displays deliver quality, but you expect more. This display features enhanced Full HD 1920×1080 resolution. With Full HD for crisp detail paired with high brightness, incredible contrast and realistic colours, expect a true-to-life picture.

TrueVision





TrueVision On TrueVision Off

TrueVision is a proprietary Philips technology that uses an advanced algorithm for testing and aligning monitor display, which gives you the ultimate display performance. Philips ensures that TrueVision monitors leave the factory fine-tuned with this process giving you consistent colour and picture quality.

Specifications

Please note that this is a pre-sales leaflet. The contents of this leaflet reflect the best of our knowledge per date and country mentioned above. The contents of this leaflet are subject to change without notice. Philips does not accept any liability as to the contents of this leaflet.

Picture/Display

LCD panel type
Backlight type
Panel Size
Panel Size
Effective viewing area
Aspect ratio
Optimum resolution
SmartResponse
(typical)
Brightness
AH-IPS LCD
W-LED system
27 inch/68.6 cm
597.89 (H) x 336.31 (V)
16:9
1920 x 1080 @ 60 Hz
5 ms (Grey to Grey)
(typical)
Brightness
250 cd/m²

Brightness 250 cd/m Contrast ratio 1000:1

(typical)

SmartContrast 20,000,000:1

Pixel pitch 0.311 x 0.311 mm (0.012" x 0.012")

Viewing angle 178° (H)/178° (V) @ C/R > 10 Picture enhancement SmartImage Lite

Display colours 16.7 M Scanning Frequency 30–83 kHz (H)/56–75 Hz (V)

MHL 1080p@30Hz sRGB Yes

Connectivity

Signal Input HDMI (digital, HDCP)
MHL-HDMI (digital, HDCP)

VGA (Analogue) Separate Sync

Sync Input Separate Sync Sync on Green

data subject to change 2017, August 4

Audio (In/Out) PC audio-in

Headphone out

Convenience

Built-in Speakers 6W x 2

User convenience Power On/Off Menu

Volume Input SmartImage Lite

OSD Languages Brazil Portuguese

Czech Dutch English Finnish French

German Greek Hungarian Italian Japanese Korean Polish

Portuguese Russian Simplified Chinese Spanish

Swedish Traditional Chinese

Turkish Ukrainian

Other convenience Kensington lock

VESA mount (100 x 100 mm) Plug and Play DDC/CI

Compatibility Mac OS X sRGB

Windows 7 Windows 8

Stand

Tilt -5/20 degree

Power

On mode 25.6 W (EnergyStar 6.0 test method)

0.5 W (typ.) Standby mode 0.3 W (typ.) Off mode Operation - White Power LED indicator

Standby mode - White (flashing)

Power supply External

100-240 VAC, 50-60 Hz

Dimensions

(mm)

Product with stand

622 x 470 x 237 mm

Product without 622 x 375 x 46 mm

stand (mm)

Packaging in mm (W 667 x 546 x 106 mm

x H x D

Weight

Product with stand 5.10 kg

(kg)

Product without 4.88 kg stand (kg)

Product with packaging (kg)

7.14 kg

Operating conditions

Temperature range

(operation)

Temperature range

(storage)

Relative humidity

20%-80% % Altitude

Operation: +12,000 ft (3658 m), Nonoperation: +40,000 ft (12,192 m)

0°C to 40°C °C

-20°C to 60°C °C

MTBF 30,000 hour(s)

Sustainability

Environmental and

energy

EnergyStar 6.0 EPEAT Silver RoHS Lead-free Mercury Free

100 %

Recyclable packaging

material

Compliance and standards

Regulatory Approvals **BSMI**

CE Mark cETLus FCC Class B GOST SASO **SEMKO** TCO 6.0

TUV/ISO9241-307

WEEE

Cabinet

White Colour Finish Glossy

* Requires optional MHL-certified mobile device and MHL cable (not included). Please check with your MHL device vendor for compatibility.

* Standby/Off energy saving of ErP is not applicable for the MHL charging functionality

* "IPS" word mark / trademark and related patents on technologies belong to their respective owners.



data subject to change 2017, August 4

EAN: 8712581717193

Version: 2.0.1

© 2017 Koninklijke Philips N.V.

All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.