

Acer V7 series

Acer V277bip

Maintain focus and comfort in the workplace in ergonomic bliss with maximum visibility. The ZeroFrame bezel design with narrower borders offers more space for viewing.

Work in finer detail with high resolution IPS screens that give you plenty of working space with exceptional viewing angles. What's more, if you place monitors next to each other, the ZeroFrame design ensures an almost uninterrupted view.

The latest interfaces connect the Acer V7 series quickly and easily with your devices.



- Diagonal size: 68.6 cm (27.0 inches)
- Resolution (native): 1,920 x 1,080
- Response time: 4 ms
- Brightness: 250 cd/m²
- Connectivity: VGA, HDMI, DP



















Acer V277bip SPECIFICATIONS







Technical specifications

68.6 cm (27.0 inches) Diagonal size Active display area (WxH) 597 x 336 mm Resolution (native) 1,920 x 1,080 Aspect ratio 16:9 Pixel pitch (PPI) 0.311 mm (81.6) IPS Technology Panel type Response time 4 ms Brightness 250 cd/m² Backlight type LFD

No, anti-glare display 178°/178° Acer CrystalBrite Viewing angle (h/v) CR>10:1 Viewing angle (h/v) CR>5:1 178°/178° Static contrast ratio 1000:1 100M:1 Dynamic contrast ratio 16.7M Colors 100% sRGB Color space Connectivity VGA, HDMI, DP Black Matt Chassis colour 30-80KHz / 55-75Hz Frequency (H/V) Refresh rate (max.) 75 Hz

Power supply and consumption

 Power supply
 Internal

 Min On
 16.17 W

 Sleep
 0.42 W

 Off/Standby
 0.37 W

 Energy Efficiency Class
 A+

 Annual Energy Consumption
 24 kWh

ErgoStand

 $\begin{array}{ll} \mbox{Tilt angle} & -5\mbox{°^{\sim}}\,25\mbox{°} \\ \mbox{VESA wall mounting} & 100\mbox{x}100\mbox{ mm} \end{array}$

Norms and Standards

 $\begin{array}{lll} \text{Guarantee} & 36 \, \text{Months Carry In} \\ \text{MTBF} & 30,000 \, \text{h at } 25^{\circ}\text{C} \end{array}$

Dimensions and weight

 Dimension (Wx Hx D)
 614 x 464 x 207 mm

 Min. thickness without stand
 66 mm

 Weight (unpacked)
 8.88 kg

 Weight (packed)
 9.93 kg

 Pallet qty and size (Hx Wx D)
 59 Pcs (215.4 x 113.1 x 127.8 cm)

 Container loading (20'/40')
 472 / 1,062

Others

OSD languages EN, DE, ES, NL, FR, IT, FI, RU, P, CN, PL
Operating ambient temperature 0°C to 40°C
Operating ambient humidity 20% to 80%
Storage ambient temperature -20°C to 60°C

Ordering Informations

Model V277bip
Part number UM.HV7EE.004
EAN 4713883600774
Package content EU power cable (1,8m), VGA cable (1,8m), DisplayPort cable (1,8m), quick start guide