Datasheet

HP LD5512 4K UHD Conferencing Display



A big-screen showcase for your best brainstorming

Inspire collaboration and productivity among small and medium groups with the extra-large HP LD5512 4K UHD Display. Show and share every detail in 3840 x 2160 resolution on a 139.7 cm (55") diagonal screen with integrated dual stereo speakers.



See it all

• Experience excellent content readability and brilliant imagery from more than 8 million pixels and 3840 x 2160 resolution. Get great views from across the room with 178-degree wide viewing angles.

Partner with a collaboration-enhanced PC

Pair the display with an HP Elite Slice for Meeting Rooms, HP Collaboration PC with optional Intel Unite® solution¹
or HP Chromebox to turn your everyday conference room into a world-class collaboration center.

Set up in moments

Quickly connect to your video source with DisplayPort™, HDMI or VGA. Enjoy stereo audio from two integrated 6W speakers and control settings with the included remote.

Featuring

- Use the display on an optional stand1 in conference rooms and workspaces where you need large-scale views of data and content, or mount² on a wall in small spaces with the integrated VESA mount.³
- Rest assured that your IT investment is supported by a three-year standard limited warranty.

HP LD5512 4K UHD Conferencing Display Specifications Table







Display size (diagonal) 139.7 cm (55°) Display Typo ADS will ED backlight Ponel Active Area 120.96 x 88.04 cm; Viewing Angle 178° horizontal; 178° vertical Brightness 350 cd/m²¹ Contrast Ratio 1200 static! Response Ratio 8 ms gray to gray¹ Aspect Ratio 16.09 Native Resolution 4K UHD (3840 x 2160 @ 60 Hz) Resolutions Supported 3840 x 2160; 2560 x 1440; 1920 x 1080; 1600 x 1200; 1680 x 1050; 1440 x 900; 1280 x 1024; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; Lanquage selection; LED Backlights; 0n-screen controls; Plug and Play; User programmable; Asset Control; Anti-static User Controls Auto: Input Control; Menu; Minus (***); OK; Plus (***); Power Input jower I USA; 1 HDMI 2.0; 2 HDMI 1.4; 1 Display-port** and HDMI Ports and Connectors 1 USB; 2 HDMI 1.4; 1 Display-port** and HDMI Power consumption Panel Active Area: 120.96 x 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD Dimensions with out Stand (W. x) 124.16 x 77.97 x 23.74 cm D'Inventions without Stand (W. x) 124.16 x 77.97 x 23.74 cm	Product Color	Black and Silver
Panel Active Area 120,96 x 68.04 cm; Viewing Angle 178° horizontal; 178° vertical Brightness 350 cd/m² Contrast Ratio 1200:1 static¹ Response Ratio 8 ms gray to gray¹ Aspect Ratio 16:09 Native Resolution 4K UHD (3840 x 2160 @ 60 Hz) Resolutions Supported 3840 x 2160; 2560 x 1600; 2560 x 1440; 1920 x 1080; 1600 x 1200; 1680 x 1050; 1440 x 900; 1280 x 1024; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable; Asset Control; Anti-static User Controls Auto, Horizon, Menu; Minus ("-"), OK; Plus ("+"); Power Input signal 176°, 11MDI 2.0; 21MDI 1.4; 1 DisplayPort™ 1.2 with HDCP support on DisplayPort™ and HDMI Ports and Connectors 1758 2.0 Ilmost John Without Stand (W x D x 124.16 x 77.97 x 23.74 cm + H) H) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm + H) Dimensions without Stand (W x 124.16 x 77.2.12 x 69.9mm D x H) Weight 14.4 kg (With stand) Multimedia Two 6 W integrated speakers Certification and Compliance Controls (NCC); HOSS Green Mark; 25.1ETR-CP No.27(VOC); IIS C 61000-3-2; PSE(160950) Environmental Mercury-free display backlights Envery Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Display size (diagonal)	139.7 cm (55")
Viewing Angle 178° horizontal; 178° vertical Brightness 350 cd/m²¹ Contrast Ratio 12001 static¹ Response Ratio 8 ms gray to gray¹ Aspect Ratio 1609 Native Resolution 4K UHD (3840 x 2160 @ 60 Hz) Resolutions Supported 3840 x 2160 @ 500 x 1500 x 2560 x 1600 x 1200 x 1600 x 1200 x 1680 x 1050; 1440 x 900; 1280 x 1024; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable; Asset Control; Anti-static User Controls Auto; Input Control; Menu; Minus (*-"); OK; Plus (*+"); Power Input signal 1 V.GA.; 1HDML 2.0; 2 HDML 1.4; 1 DisplayPort™ 1.2 with HDCP support on DisplayPort™ 1.2 cable; Documentation; HDMI cable What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Display Type	ADS w/LED backlight
Brightness 350 cd/m²¹ Contrast Ratio 1200:1 static¹ Response Ratio 8 ms gray to gray¹ Aspect Ratio 16:09 Native Resolution 4K UHD (3840 x 2160 @ 60 Hz) Resolutions Supported 3840 x 2160; 2560 x 1600; 2560 x 1440; 1920 x 1080; 1600 x 1200; 1680 x 1050; 1440 x 900; 1280 x 1024; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable; Asset Control, Anti-static User Controls Auto; Input Control; Menu; Minus (*-*); OK; Plus (*-*); Power Input signal 1VGA; 1 HDMI 2.0; 2 HDMI 1.4; 1 DisplayPort™ 1.2 with HDCP support on DisplayPort™ and HDMI Ports and Connectors 1USB 2.0¹ Input power Input voltage: 100 to 240 VAC Power consumption Panel Active Area: 120.96 x 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD (3840 x 2150 @ 60 Hz) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm +1) Dimensions without Stand (W x D x 124.16 x 77.97 x 23.74 cm +1) Dimensions without Stand (W x D x 124.16 x 77.97 x 23.74 cm +1) Weight 14.4 kg (With stand) Multimedia Two 6 W integrated speakers Certification and Compliance Circlification and Compliance WCC; J-MOSS Green Mark; 25JEITA-CP No.27(VOC); JIS C 61000-3-2; PSE(J60950) Ernvironmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Panel Active Area	120.96 x 68.04 cm;
Contrast Ratio 120: 1 static¹ Response Ratio 8 ms gray to gray¹ Aspect Ratio 16:09 Native Resolution 4K UHD (3840 x 2160 @ 60 Hz) Resolutions Supported 3840 x 2160; 2560 x 1600; 2560 x 1440; 1920 x 1080; 1600 x 1200; 1680 x 1050; 1440 x 900; 1280 x 1024; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable; Asset Control; Anti-static User Controls Auto; Input Control; Menu; Minus (***); OK; Plus (****); Power Input signal 1 VGA; 1 HDMI 2.0; 2 HDMI 1.4; 1 DisplayPort** 1.2 with HDCP support on DisplayPort** and HDMI Ports and Connectors 1 USB 2.0¹ Input power Input voltage: 100 to 240 VAC Power consumption Panel Active Area: 120.96 x 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD (3840 x 2160 @ 60 Hz) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm H) Dimensions without Stand (W x D x 124.16 x 77.97 x 23.74 cm H) Weight 14.4 kg (With stand) Multimedia Two 6 W integrated speakers Certification and Compliance (VCC); J-MOSS Green Mark; 25JEITA-CP No.27(VOC); JIS C 61000-3-2; PSEU60950) Environmental Mercury-free display backlights Energy Efficiency Compliance (ENERGY STAR® certified) What's in the box AC power cord; DisplayPort** 1.2 cable; Documentation; HDMI cable	Viewing Angle	178° horizontal; 178° vertical
Response Ratio 8 ms gray to gray' Aspect Ratio 16:09 Native Resolution 4K UHD (3840 x 2160 @ 60 Hz) Resolution 5upported 3840 x 2160; 2560 x 1600; 2560 x 1440; 1920 x 1080; 1600 x 1200; 1680 x 1050; 1440 x 900; 1280 x 1024; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable; Asset Control; Anti-static User Controls Auto; Input Control; Menu; Minus ("-"); OK; Plus ("+"); Power Input signal 1 VGA; 1 HDMI 2.0; 2 HDMI 1.4; 1 DisplayPort™ 1.2 with HDCP support on DisplayPort™ and HDMI Ports and Connectors 1 USB 2.0¹ Input power Input voitage: 100 to 240 VAC Power consumption Panel Active Area: 120.96 x 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD (3840 x 2160 @ 60 Hz) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm H) Dimensions without Stand (W x 124.16 x 72.12 x 69.9mm D x H) Weight 14.4 kg (With stand) Multimedia Two 6 W Integrated speakers Certification and Compliance VCC; J-MGSS Green Mark; 25 JEITA-CP No.27(VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Brightness	350 cd/m ²¹
Aspect Ratio 16:09 Native Resolution 4K UHD (3840 x 2160 @ 60 Hz) Resolutions Supported 3840 x 2160; 2560 x 1600; 2560 x 1440; 1920 x 1080; 1600 x 1200; 1680 x 1050; 1440 x 900; 1280 x 1024; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable; Asset Control; Anti-static User Controls Auto; Input Control; Menu; Minus ("-"); OK; Plus ("+"); Power Input signal 1 VGA; 1 HDMI 2.0; 2 HDMI 1.4; 1 DisplayPort™ 1.2 with HDCP support on DisplayPort™ and HDMI Ports and Connectors 1 USB 2.0¹ Input power Input voltage: 100 to 240 VAC Power consumption Panel Active Area: 12.096 x 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD (3840 x 2160 @ 60 Hz) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm H) Dimensions without Stand (W x D x 124.16 x 77.12 x 69.9mm D x H) Weight 14.4 kg (With stand) Multimedia Two 6 W integrated speakers Certification and Compliance VCC; J-MOSS Green Mark; 25 JEITA-CP No.27 (WOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Contrast Ratio	1200:1 static¹
Native Resolution 4K UHD (3840 x 2160 @ 60 Hz) Resolutions Supported 3840 x 2160; 2560 x 1600; 2560 x 1440; 1920 x 1080; 1600 x 1200; 1680 x 1050; 1440 x 900; 1280 x 1024; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable; Asset Control; Anti-static User Controls Auto; Input Control; Menu; Minus (""); OK; Plus (""); Power Input signal 1 VGA; 1 HDMI 2.0; 2 HDMI 1.4; 1 DisplayPort™ 1.2 with HDCP support on DisplayPort™ and HDMI Ports and Connectors 1 USB 2.0¹ Input power Input voltage: 100 to 240 VAC Power consumption Panel Active Area: 120.96 x 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD (3840 x 2160 @ 60 Hz) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm H) Dimensions without Stand (W x 124.16 x 72.12 x 69.9mm Dx H) Multimedia Two 6 W integrated speakers Certification and Compliance VCC; J-MOSS Green Mark; 25 JEITA-CP No.27(VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Response Ratio	8 ms gray to gray ¹
Resolutions Supported 3840 x 2160; 2560 x 1560; 2560 x 1440; 1920 x 1080; 1600 x 1200; 1680 x 1050; 1440 x 900; 1280 x 1024; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Display Features Anti-glare; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable; Asset Control; Anti-static User Controls Auto; Input Control; Menu; Minus ("-"); OK; Plus ("+"); Power Input signal 1 VGA; 1 HDMI 2.0; 2 HDMI 1.4; 1 DisplayPort™ 1.2 with HDCP support on DisplayPort™ and HDMI Ports and Connectors 1 USB 2.0¹ Input voltage: 100 to 240 VAC Power consumption Panel Active Area: 120.96 x 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD (3840 x 2160 @ 60 Hz) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm H) Dimensions without Stand (W x 124.16 x 77.97 x 23.74 cm H) Dimensions without Stand (W x 124.16 x 77.12 x 69.9mm D x H) Multimedia Two 6 W integrated speakers Certification and Compliance VCC; J-MOSS Green Mark; 25.JEITA-CP No.27(VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Aspect Ratio	16:09
x 600; 720 x 400; 640 x 480 Display Features Anti-glare; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable; Asset Control; Anti-static User Controls Auto; Input Control; Menu; Minus ("-"); OK; Plus ("+"); Power Input signal 1 VGA; 1 HDMI 2.0; 2 HDMI 1.4; 1 DisplayPort™ 1.2 with HDCP support on DisplayPort™ 1.2 with HDCP support on DisplayPort™ and HDMI Ports and Connectors 1 USB 2.0¹ Input power Input voltage: 100 to 240 VAC Power consumption Panel Active Area: 120.96 x 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD (3840 x 2160 @ 60 Hz) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm H) Dimensions without Stand (W x 124.16 x 72.12 x 69.9mm Dx+l) Weight 14.4 kg (With stand) Multimedia Two 6 W integrated speakers Certification and Compliance VCCI; J-MOSS Green Mark; 25 JEITA-CP No.27(VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Native Resolution	4K UHD (3840 x 2160 @ 60 Hz)
User Controls Auto; Input Control; Menu; Minus ("-"); OK; Plus ("+"); Power Input signal 1 VGA; 1 HDMI 2.0; 2 HDMI 1.4; 1 DisplayPort™ 1.2 with HDCP support on DisplayPort™ and HDMI Ports and Connectors 1 USB 2.0¹ Input power Input voltage: 100 to 240 VAC Power consumption Panel Active Area: 120.96 x 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD (3840 x 2160 @ 60 Hz) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm H) Dimensions without Stand (W x 124.16 x 72.12 x 69.9mm D x H) Weight 14.4 kg (With stand) Multimedia Two 6 W integrated speakers Certification and Compliance VCCI; J-MOSS Green Mark; 25 JEITA-CP No.27 (VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Resolutions Supported	
Input signal 1 VGA; 1 HDMI 2.0; 2 HDMI 1.4; 1 DisplayPort™ 1.2 with HDCP support on DisplayPort™ and HDMI Ports and Connectors 1 USB 2.0¹ Input power Input voltage: 100 to 240 VAC Power consumption Panel Active Area: 120.96 x 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD (3840 x 2160 @ 60 Hz) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm H) Dimensions without Stand (W x 124.16 x 72.12 x 69.9mm D x H) Weight 14.4 kg (With stand) Multimedia Two 6 W integrated speakers Certification and Compliance VCCI; J-MOSS Green Mark; 25JEITA-CP No.27(VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Display Features	Anti-glare; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable; Asset Control; Anti-static
with HDCP support on DisplayPort™ and HDMI Ports and Connectors 1 USB 2.0¹ Input power Input voltage: 100 to 240 VAC Power consumption Panel Active Area: 120.96 x 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD (3840 x 2160 @ 60 Hz) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm H) Dimensions without Stand (W x 124.16 x 72.12 x 69.9mm D x H) Weight 14.4 kg (With stand) Multimedia Two 6 W integrated speakers Certification and Compliance VCCI; J-MOSS Green Mark; 25 JEITA-CP No.27 (VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	User Controls	Auto; Input Control; Menu; Minus ("-"); OK; Plus ("+"); Power
Input power Input voltage: 100 to 240 VAC Power consumption Panel Active Area: 120.96 x 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD (3840 x 2160 @ 60 Hz) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm H) Dimensions without Stand (W x 124.16 x 72.12 x 69.9mm D x H) Weight 14.4 kg (With stand) Multimedia Two 6 W integrated speakers Certification and Compliance VCCI; J-MOSS Green Mark; 25 JEITA-CP No.27 (VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Input signal	
Power consumption Panel Active Area: 120.96 × 68.04 cm; Power consumption Description: 130 W (maximum), 90 W (typical), 0.5 W (standby); Screen resolution: 4K UHD (3840 × 2160 @ 60 Hz) Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm H) Dimensions without Stand (W x 124.16 x 72.12 x 69.9mm D x H) Weight 14.4 kg (With stand) Multimedia Two 6 W integrated speakers Certification and Compliance VCCI; J-MOSS Green Mark; 25 JEITA-CP No.27 (VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Ports and Connectors	1 USB 2.01
(3840 x 2160 @ 60 Hz)Dimensions with Stand (W x D x 124.16 x 77.97 x 23.74 cm H)Dimensions without Stand (W x 124.16 x 72.12 x 69.9mm D x H)Weight 14.4 kg (With stand)Multimedia Two 6 W integrated speakersCertification and Compliance VCCI; J-MOSS Green Mark; 25JEITA-CP No.27(VOC); JIS C 61000-3-2; PSE(J60950)Environmental Mercury-free display backlightsEnergy Efficiency Compliance ENERGY STAR® certifiedWhat's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Input power	Input voltage: 100 to 240 VAC
H) Dimensions without Stand (W x 124.16 x 72.12 x 69.9mm D x H) Weight 14.4 kg (With stand) Multimedia Two 6 W integrated speakers Certification and Compliance VCCI; J-MOSS Green Mark; 25 JEITA-CP No.27 (VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Power consumption	
D x H) Weight 14.4 kg (With stand) Multimedia Two 6 W integrated speakers Certification and Compliance VCCI; J-MOSS Green Mark; 25JEITA-CP No.27(VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable		< 124.16 x 77.97 x 23.74 cm
Multimedia Two 6 W integrated speakers Certification and Compliance VCCI; J-MOSS Green Mark; 25JEITA-CP No.27(VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable		124.16 x 72.12 x 69.9mm
Certification and Compliance VCCI; J-MOSS Green Mark; 25JEITA-CP No.27(VOC); JIS C 61000-3-2; PSE(J60950) Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Weight	14.4 kg (With stand)
Environmental Mercury-free display backlights Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Multimedia	Two 6 W integrated speakers
Energy Efficiency Compliance ENERGY STAR® certified What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Certification and Compliance	VCCI; J-MOSS Green Mark; 25JEITA-CP No.27(VOC); JIS C 61000-3-2; PSE(J60950)
What's in the box AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable	Environmental	Mercury-free display backlights
	Energy Efficiency Compliance	ENERGY STAR® certified
Warranty 3 year limited warranty including 3 year of parts and labour. Certain restrictions and exclusions apply.	What's in the box	AC power cord; DisplayPort™ 1.2 cable; Documentation; HDMI cable
	Warranty	3 year limited warranty including 3 year of parts and labour. Certain restrictions and exclusions apply.

HP LD5512 4K UHD Conferencing Display

Accessories and services (not included)

HP DSD Security Wall Mount



HP offers a variety of optional products (each sold separately) designed to complement our monitors and enhance the overall computing and viewing experience. The HP Digital Signage Wall Mount Solution with Quick Release and Security Plate is the newest option designed for use with HP-branded LCD digital signage displays. The wall mount has a 90-degree pivot for use in landscape or portrait position, and can be used in tandem with an HP 8000 Series USDT PC or compatible thin client to create a complete hardware solution for HP customers.

Product number: Z2J20AA

HP 5 year Next business day XLarge Monitor Only Hardware Support

Receive 5 years of next business day onsite HW Support from an HP-qualified technician for your computing device, if the issue cannot be solved remotely.

Product number: UE370E



HP LD5512 4K UHD Conferencing Display

Messaging Footnotes

¹ Sold as a configurable option at the time of purchase.

Technical specifications disclaimers

¹ All specifications represent the typical specifications provided by HP's component manufacturers, actual performance may vary either higher or lower.

Sign up for updates

www.hp.com/go/getupdated



² Stand and wall mounting hardware sold separately.