

Everyday Productivity

Expand your view and your productivity with this 54.5 cm (21.45-inch) diagonal, FHD monitor when you're working or learning. This sleek, sizeable monitor makes computing easy and complete via a crisp, smooth screen and simple design, so you can do more everyday.



In Full View

Enjoy how your projects or assignments look on this monitor with excellent, front-of-screen views. It boasts FHD resolution and AMD FreeSync™ technology featuring a 75Hz refresh rate¹ for sharp images and fluid motion.

Modern Design. Functional Fit.

Clear your mind and your desk with a monitor designed to work in any space. Keep the focus on your screen through the sleek profile, neat cable management, and slim stand with adjustable tilt for your perfect view.

Intuitive Inputs. Easy Control.

Make your workspace as simple as possible, so you can concentrate on what you do best. Easily setup your monitor by customizing your settings with the intuitive Joypad OSD button or manage them directly from the screen with HP Display Center².

Reduce. Repurpose. Recycle.

To do more for the planet, we are helping to close the loop by repurposing IT equipment in our newest EPEAT® registered³ and ENERGY STAR® monitors. To go above and beyond, these monitors contain 85% recycled plastics solely from recycled ITE plastics⁴. Plus, this monitor ships in 100% recyclable packaging⁵.

Featuring

75 Hz Refresh Rate

Experience smooth, life-like video and clear detail with a 75 Hz refresh rate that provides fluid movement from frame to frame.¹

Narrow bezel display

By squeezing a larger screen into a smaller frame, this narrow bezel optimizes your display's appearance with an efficient design.

Easy Joypad OSD Button

It's never been easier to configure your display with the Joypad OSD button to adjust brightness, resolution, and volume.

Low Blue Light Mode

Keep your eyes comfortable with subtly warmer display colors onscreen.

With the Environment in Mind

Meeting the latest standards with EPEAT® registered, ENERGY STAR® and TCO certifications.³

Thoughtful Product Packaging

We use 100% recyclable packaging that meets recycling requirements, so it can stay out of the landfill. 5,6

Neat Cable Management

Neat cable management solution for a cleaner workspace and more productivity.

HP Display Center

Customize your display with easy, intuitive HP Display Center software that lets you tailor your settings, partition screens, and even dim the screen.2

AMD FreeSync™

AMD FreeSync™ technology provides smooth, tear-free videos by reducing input latency, screen tearing, and stuttering.⁷

⁶ Recycling facilities not available in all locations.
7 FreeSync™ is only available when it is connected on Display Port or HDMI. FreeSync is an AMD® technology is enabled on FHD or QHD displays AMD Radeon Graphics and/or AMD A-Series APU-compliant monitors with DisplayPort/HDMI Adaptive-Sync required. AMD 15.11 Crimson driver (or newer) required to support FreeSync over HDMI. Adaptive refresh rates vary by monitor. More information is available at www.amd.com/freesync.







	Does does to complete	COCK I
	Product number	65P56AA (ADM) 106E/R10326A- (ADM) 106E/R10320E- (ADD) 106E/R103232- (ADT) 106E/R1032AD- (ADD) 106E/R1032A
		196548414116; (UuG) 196548193585; (UUZ) 196548193615
Description Signification Classification Section Description Section Projection Section Registry Section Resistance speciment 1400-000-000-000-000-000-000-000-000-000	•	
Description 524 selderm Registration 254 selderm Registration 254 selderm Registration 2016 selderm Registration 2016 selderm Collegement Solgment 1000 control Collegement Solgment 1000 control Registration and control 1000 control Resident Segment 600 control	-	
	- <u>-</u>	
Opened sold 2010 1 Contact sold 2000 1 Trobust control (prosportment polyment) 2000 1000 1 Trobust control (prosportment polyment) 2000 1000 1 Productor (prosportment) 2000 1000 1 Residutor (prosportment) 4000 1000 1000 1000 1000 1000 1000 1000	-	
Operations ASSOCIATION Object some state departed ASSOCIATION Production ASSOCIATION Permission of production ASSOCIATION Permission of production ASSOCIATION (ASSOCIATION ASSOCIATION AS		
Design and carbidy and a contract of the contract of th		
	-	
Part		
Description 58 bit 50 bit	Product color	
Displys cane frequency before cane 54.54.518* Displys freather frequency before cane 45.7512 Displys features 55.7512 Displys features 55.7512 Physical cane frequency before 56.7512 Displys features	Resolution (maximum)	FHD (1920 x 1080 @ 75 Hz) ¹
Display Infortace 49.57.500 Display Infortace 0.00 content controls; MD Predyun**; too bilangit mode Anti-glane Physical Activity Refeature 40.00 content controls; MD Predyun**; too bilangit product Anti-glane Physical Activity Refeature 40.00 control production of the Section of Miss assimably sourced and registed 65% pod-consent registed 65% pod-consent production (Infortance of Missach 11 M Injustice) Physical Activity Refeature 40.00 controls presented and prediction (Infortance of Missach 11 M Injustice) Object under Colors 40.00 STAN Controls (Information of Missach 11 M Injustice) 40.00 STAN Controls (Information of Missach 12 M Injustice) 40.00 STAN Controls (Information of Missach 12 M Injustice) 40.00 STAN Controls (Information of Missach 12 M Injustice) 40.00 STAN Controls (Information of Missach 12 M Injustice) 40.00 STAN Controls (Information of Missach 12 M Injustice) 40.00 STAN Controls (Information of Missach 12 M Injustice) 40.00 STAN Controls (Information of Missach 12 M Injustice) 40.00 STAN Controls (Injustice) 40.00 STAN Controls (Injustice) 40.00 STAN Controls (Injustice) 40.00 STAN	Resolutions supported	640 x 480; 720 x 400; 800 x 600; 1024 x 768; 1280 x 720; 1280 x 800; 1280 x 1024; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080
Display features On-scene controls, MPO Treating, ************************************	Display scan frequency (horizontal)	54-84.3 kHz
Popular decentry features Secretal y features Secretal y features Controllments decendations Modern popular public control to 100% substancibly sourced and recycliable 150% produce consume recycled priodic 100% ITT-denied closed storage from the Vision of Production (Production of Production Control). The American Control of Production (Production Control). The American Control of Production Control of Production (Production Control of Production Control of P	Display scan frequency (vertical)	48-75 Hz
Environmental specifications Moised poper pub custion insoit boals in 100% sostainably sourced and recydable; 65% post-consumer recycled plastic (100% ITT-devised closed loop plastic (100% ITT-devised closed loop plastic); boar lettings in 141% placed. Bodge Mark Combistors Develope the Combistor (100%) Processor (100%) <th< th=""><th>Display features</th><th>On-screen controls; AMD FreeSync™; Low blue light mode; Anti-glare</th></th<>	Display features	On-screen controls; AMD FreeSync™; Low blue light mode; Anti-glare
Exercise efficiency Energy efficiency class E, CN mode power communition 21 W (invasimum). Standing 0.5 W (standing), Power communition Chromodinal 11 W (bypoint) Disably Liver Control (bridge) 5 to 357 Operating hamperature range 6 to 357 Operating hamperature range 2 to 300 MP. Operating hamperature range 2 to 300 MP. Operating hamperature range 2 to 300 MP. Power supply 100 - 200 MP. VES. Introduction Standing A. (See See See See See See See See See Se	Physical security features	Security lock-ready ¹⁰
Days by User Cartent Options Proce control, Brightness, Earl, Menia control, Paper control, Hangement University Obserable premerature range 5 19 % Obserable premerature range 4 14 100 FF Obserable principal punishing range 2 14 100 FF Ecolubes 100 - 200 WES (Solicial) WEST Amouth 100 - 200 WES (Solicial) WEST Amouth 100 - 200 WES (Solicial) WEST Amouth 100 - 200 WEST (Solicial) WEST Amouth 100 Feet WEST Amouth 100 Feet Amouth WEST Amouth 100 Feet WEST Amouth 100 Feet Amouth	Environmental specifications	Molded paper pulp cushion inside box is 100% sustainably sourced and recyclable; 85% post-consumer recycled plastic; 100% ITE-derived closed loop plastic; Low Halogen 5.6.7.8
Opensing temperature range 51 5 35°C Opensing temperature range 41 10 5°T Ceclusies 2016 50°R Coultables 2016 50°R registred. TOL Certified configurations available! ENRIFO'S New certified Power supply 100 - 200 mon 100 mm 2 Political discressis Wilders Deptat Height 400 mm 100 mm 2 Political discressis Wilders Deptat Height 100 mm 100 mm 2 Political discressis Wilders Deptat Height 100 mm 100 mm 2 Political discressis Wilders Deptat Height 100 mm 100 mm 2 Political discressis Wilders Deptat Height 100 mm 100 mm 2 Political discressis Wilders Deptat Height 100 mm 100 mm 2 Political discressis Wilders Deptat Height 100 mm 100 mm 2 Political discressis Wilders Deptat Height 100 mm 100 mm 2 William Deptat Height 100 mm 200	Energy efficiency	Energy efficiency class: E; On-mode power consumption: 21 W (maximum); Standby: 0.5 W (standby); Power consumption (on-mode): 21 W (maximum); Power consumption (off-mode): 11 W (typical)
Operating temperature range 41 to 555* Operating by Invitoly range 20to 300 RRI Excludes 100 - 240 WK 50160 Hz VEX. mont 100 - 240 WK 50160 Hz Place of supply 100 - 240 WK 50160 Hz Place of supply 100 - 240 WK 50160 Hz Place of supply 100 - 240 WK 50160 Hz Place of supply 100 - 240 WK 50160 Hz Place of supply 100 - 240 WK 50160 Hz Place of supply 100 - 240 WK 50160 Hz Place of supply 100 - 240 WK 50160 Hz Place of supply 100 - 240 WK 50160 Hz Place of supply 100 - 240 WK 50160 Hz Place of supply 100 - 240 WK 50160 Hz Place of supply 100 - 240 WK 50160 Hz Place of supply 100 Pc Vertical sharp angle of supply 100 Pc Value of supply 100 Pc <th>Display User Control Options</th> <th>Power control; Brightness; Exit, Menu control; Input control; Information; Color control; Image control; Management</th>	Display User Control Options	Power control; Brightness; Exit, Menu control; Input control; Information; Color control; Image control; Management
Operating humidly range 20 to 80% RSH Ecobels DEAD Registered, TO Certified configurations available*, ENERDY STAP® certified Power supply 10 - 24 on WC 500 MBH VESA mount 10 - 24 on WC 500 MBH Palled chronarious Width A (Debt.) A signal 60 - 24 on WC 500 ABM Palled strends width A (Debt.) A signal 61 on TI AL A 200 ABM Palled strends width A (Debt.) A signal 10 on TI AL A 200 ABM Palled strends width A (Debt.) A signal 10 on TI AL A 200 ABM Palled strends width A (Debt.) A signal 10 on TI AL A 200 ABM Palled strends width A (Debt.) A signal 10 on TI AL A 200 ABM Palled strends width A (Debt.) A signal 10 on TI AL A 200 ABM Rock 4 on Ti AL A 200 ABM Rock 1 on Ti AL A 200 ABM Rock (Ti AL A 200	Operating temperature range	5 to 35°C
Ecobabes EPENT* registered, TOC certified configurations available**, EPERT* STAR* certified	Operating temperature range	41 to 95°F
Power supply 100 - 240 W/C 50/60 Hz VES Amount 100 mm x 100 mm ¹² Pollet dimensions (Width x Depth x Height) 68 8 x 113.4 x 2063 cm Pools per Inch (pg) 103 pg Ponel bit deeth 8 bit (6 bit = FBC) Vertical Weingrangie 170* Metocontal Weingrangie 170* Bozek Narrow Brachens 31 Redness 31 Redness 31 il Pollet pit modes Ves (TÜV certified) Poll tay of Line (Line	Operating humidity range	20 to 80% RH
VESA mount 100 mmx 100 mm 12 mm Pallet dimensions (Width X peth x Height) 56 x 113 4 x 26.63 cm Pavels per levit (pgl) 103 pgl Pavel but (peth) 8 bit (6 bt + FRO) Vertical Vewing angle 178* Horizontal Vewing angle 178* Bazel Narrow Ill 5 to +23* Hardness 3H Screen treatment Acti-glare Flicker-free Ves (TDV certified) Low base light modes Ves (TDV certified) Port and Connectors 1 VGC 1 HDN 1.4 HDCP Ves. FLDW Management software HD Display Center 11 Warranty 1 yes Interest warranty Settifications and compliances Australian-New Jesuland MEPS ISS ISS ISS ICS (CECE (EEC) CEL (EEC) EEL (SA EAC ENERGY STARP-FCC, ISO 9241-307; XE/MCC, Morozoft WHOL Certifications (NOM PSIR Brotis, SERA, TOO Certified Edge; TDV Warranty 1 yes Interest warranty Sauar ITLV ILS IL VCC, Wietman MEPS, ISEE ISS ISS ISS ICS CECE (EEC) EEL (SA EAC ENERGY STARP-FCC, ISO 9241-307; XE/MCC, Morozoft WHOL Certifications (NOM PSIR Brotis, SERA, TOO Certified Edge; TDV Warranty 5 yes 12.2 x 3.87 cm Policage weight	Ecolabels	EPEAT® registered; TCO Certified configurations available ⁴ ; ENERGY STAR® certified
Pallet dimensions (Width x Depth x Height) 96.8 x 113.4 x 206.3 cm Passe princh (pol) 103 ppl Panel bit depth 8 bit (6 bt + FRC) Vertical Verwing angle 178° Horizontal Visewing angle 178° Bized Narrow Tilt -5 to -23° Hardness 3H Screen treatment Arti-place Elicker-Fee Ves (TOV certified) Low blue light modes Ves (TOV certified) Low blue light modes Ves (TOV certified) Monagement software H Display Center 11 Monagement software H Display Center 11 Morranty Australian-New Zealand HIPS, 185. SERVIC CCC CE. CEEP, ELIC. SEALE, CEERCY STARP, FCC, ISO 3241-307, KCKC, Monasort WHID, Centrication, NOA, PSB, No46S, SERVIC CENTER, ELIC. SEALE, CERTERY STARP, FCC, ISO 3241-307, KCKC, Monasort WHID, Centrication, NOA, PSB, No46S, SERVIC CENTER, ELIC. SEALE, CERTERY STARP, FCC, ISO 3241-307, KCKC, Monasort WHID, Centrication, NOA, PSB, No46S, SERVIC CENTER, ELIC. SEALE, CERTERY STARP, FCC, ISO 3241-307, KCKC, Monasort WHID, Centrication, NOA, PSB, No46S, SERVIC CENTER, ELIC. SEALE, CERTERY STARP, FCC, ISO 3241-307, KCKC, Monasort WHID, Centrication, NOA, PSB, No46S, SERVIC CENTER, ELIC. SEALE, CERTERY STARP, FCC, ISO 3241-307, KCKC, Monasort WHID, Centrication, NOA, PSB, No46S, SERVIC CENTER, ELIC. SEALE, CERTERY STARP, FCC, ISO 3241-307, KCKC, Monasort WHID	Power supply	100 - 240 VAC 50/60 Hz
Peets per Inch (ppl) 103 ppl Panel bledeh 8 bit (6 bt - FRC) Vertical Viewing angle 178° Bezel Narrow Bezel Narrow It - 5 to - 23° Hardness 3H Sceen treatment Anti-glare Flicker-free Ves (TOV certified) Low blue light modes Ves (TOV certified) Port and Connectors 1 Ves. HDMI 1.4 MOCP Ves. HDMI Management of Warranty 4 PD Display Center 13 Warranty 1 year Inmited warranty Certifications and compliances 4 pp. Splay Spl. Spl. Spl. Spl. Spl. Spl. Spl. Spl.	VESA mount	100 mm x 100 mm ¹²
Pamel bit depth 8 bit 16 bit - FRC Vertical wewing angle 178" Hortzontal viewing angle 178" Bozel Narrow Tilt -5 to + 23" Bardness 3H Screen treatment Anti-glane Ricker-Free Ves (TÜV certified) Low bise light modes Ves (TÜV certified) Dort and Connectors 1 VGA; 1+DMI 1.4 HDCP Ves. HDMI Hangement software HP Display center 11 Warranty 1 year limited warranty Certifications and compliances Rasart TULVI LIE, VCC, Veteran MPS; NES, ESMI, CB; CC, CE; CEC, CE; CEC, CE; CEC, CE; CEC, CE; CEC, CE, CEC, CE, CEC, CE, CEC, CE, CEC, CE, CE	Pallet dimensions (Width x Depth x Height)	96.8×113.4×2063 cm
Vertical Vewing angle 178° Horizontal Vewing angle 178° Bezel Narrow Ilt -5 to +23° Hardness 3H Screen treatment Anti-glaze Filcker-Free Yes TÜV certified Low blue light modes Yes (TÜV certified) Port and Connectors 1 VGA; H HDMI 1.4 HDCP Yes, HDMI Management software HP Display Center ¹¹ Warranty 1 year limited warranty Certifications and compliances Australian-New Zealand MRES, BIS, BSM. (ER, CCC, CEC, CEC), CEL, CEA, EAC, ENEROY STARP- FCC, 150 9241-307; KC/RCC, Microsoft WHQL, Certification, NOM, PSE, RoHS, SERPA TOO Certified Edge, TUV What's in the box HDMI cable, Warranty racid, Quick Setup Poster, Doc-kit, AC, power cord? Dimensions (L, W.W.H) 50/42 x 508 x 30.3 or Weight 2.8 kg Package Dimensions (L, W.W.H) 56/7 x 12.1 x 38.7 cm Package Dimensions (L, W.W.H) 56/7 x 12.1 x 38.7 cm Package Weight 4.3 kg Pallet (layers) 6 Poolucts per Jalet 96 Polucts per Jalet 96	Pixels per inch (ppi)	103 ppi
Horizontal viewing angle 178°	Panel bit depth	8 bit (6 bit + FRC)
Bezel Narrow Tit -5 to +23** Hardness 3H Screen treatment Anti-glare Icker-free Ves (TiV certified) Low blue light modes Ves (TiV certified) Port and Connectors 1 V/GA; 1 HDM1 1.4 HDCP Ves, HDMI Management software HPD Issplay Center 11 Warranty 1 year limited warranty Certifications and compliances Australian-New Zealand MEPS; BIS; BSML (E); CCC (E; ECEP, CEL; CSA; EAC; ENERGY STARP; FCC; ISO 9241-307; KC//ACC; Microsoft WHQL Certification; NOM; PSB, RoHS; SEPA; TCO Certified; TCO Certified Edge; TLV Wars in the box HDMI called warranty and Quick Setup Poster; Doc-kit; AC power cord? Dimensions (Lx W x H) 50.42 x 5.08 x 30.3 om Weight 2.8 kg Package weight 4.3 kg Package weight 6 Products per Jalee 6 Products per Jalee 96 Products per pallet 96 Pollet dispers) 96 Pollet dispersons 96 Pollet dispersons 96 Pollet dispersons 96 <th>Vertical viewing angle</th> <th>178*</th>	Vertical viewing angle	178*
Tilt5 to +23° Hardness 3H Szeen treatment Anti-glare Yes (TÜV certified) Low blue light modes Yes (TÜV certified) Port and Connectors 1 VAC, 1 HDMI 1.4 HDCP Yes, HDMI Management software HPD Display Center ¹¹ Warranty 1 year limited warranty Certifications and compliances Baustri TUV BL, VCC, VERHAM MEPS; BIS, BSM ICB, CCC, CE; CECP, CEL, CSA; EAC, ENERGY STARP*, FCC, ISO 9241-307; KC/MCC, Macrosoft WHOL Certification, NOM; PSB; ROHS; SEPA, TO Certified Edge; TUV Blastis in the box HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord ¹⁰ Dimensions (L x W x H) 50.42 x 5.08 x 30.3 cm Weight 2.8 kg Package Dimensions (L x W x H) 56.7 x 12.1 x 38.7 cm Package weight 4.3 kg Palet (Byers) 6 Products per layer 16 Products per pallet dimensions 96.8 x 113.4 x 206.3 cm	Horizontal viewing angle	178*
Hardness 3H Screen treatment Anti-glare Flicker-free Ves (TÜV certified) Low blue light modes Ves (TÜV certified) Port and Connectors 1 VGA; 1 HDM1 1.4 HDCP Ves, HDMI Management software HPD Spilay Center ¹¹ Warranty 1 year limited warranty Certifications and compliances Australians-New Zealand MEPS; BIS; BSMt CB; CCC; ECCP; CEL: CSA EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/RCC; Microsoft WHOL Certification; NDM; PSB, RoHS; SEPA; TOC Certified; TOC Certified Edge; TUV Bart's in the box HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord® Dimensions (Lx Wx H) 50.42 x 5.08 x 30.3 cm Weight 2.8 kg Package Dimensions (Lx Wx H) 56.7 x 12.1 x 38.7 cm Package Dimensions (Lx Wx H) 6 Products per layer 16 Products per pallet 9 Pallet dimensions 9 96.8 x 113.4 x 206.3 cm		
Screen treatment Anti-glaire Flicker-free Ves (TÜV certified) Low blue light modes Yes (TÜV certified) Port and Connectors 1 VGA; 1 HDNI 1.4 HDCP Yes, HDMI Management software HP Display Center ¹¹ Warranty 1 year limited warranty Certifications and compliances Bauart; TUV IBL; VCC; Vetram MEPS, WEEE; ISC (China Energy, Label (CEL) Grade 2; California Energy Commission (CEC); WW application; KE; UAE; Ukraine certificates; TÜV Flicker free certified What's in the box HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord* Dimensions (L x W x H) 56.4 x 15.1 x 38.7 cm Package Weight 2.8 kg Package Weight 4.3 kg Palete (Jayers) 6 Products per layer 16 Products per pallet 9 Pallet dimensions 96.8 x 113.4 x 206.3 cm	Tilt	-5 to +23*
Flicker-free Yes (TÜV certified) Low blue light modes Ves (TÜV certified) Port and Connectors 1 VGA; 1 HDMI 1.4 HDCP Yes, HDMI Management software HP Display Center ¹¹ Werranty 1 year limited warranty Certifications and compliances Australian-New Zealand MEPS; BIS; BISMI; CB; CCC; CE; CECP; CEL; CSA; EAC; ENERGY STAR®; F.CC; ISO 9241-307; KC/RCC; Microsoft WHQL Certification; NDM; PSB; RoHS; SEPA; TOC Certified Edge; TUV Bauart; TUV. LBI; VCC; Vietnam MEPS; WEEE; ISC; China Energy Label (CEL) Grade 2; California Energy Commission (CEC); WW application; ICE; UAE; Ulraine certificates; TÜV Flicker free certified What's in the box HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord® Dimensions (L x W x H) 50.42 x 5.08 x 3.03 cm Package Dimensions (L x W x H) 55.7 x 12.1 x 38.7 cm Package weight 2.8 kg Pallet (Byers) 6 Products per layer 16 Products per pallet 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm	Hardness	3H
Low blue light modes Yes (TÜV certified) Port and Connectors 1 VGA; 1 HDMI 1.4 HDCP Yes, HDMI Management software HP Display Center 11 Warranty 1 year limited warranty Certifications and compliances Australian-New Zealand MPPS, BIS, BSMI; CB, CCC; CE; CECP, CEL; CSA; EAC; ENERGY STAR®, FCC; ISO 9241–307; KC/ACC; Microsoft WHQL Certification; NOM; PSB; RoHS, SEPA; TCO Certified Edge; TUV Bauart; TUV. BIL; VCC; Verlam MEPS, WEEE; ISC; China Energy Label (CEL) Grade 2; California Energy Commission (CEC); WW application; ICE; UAE; Ukraine certificates; TÜV Flicker free certified What's in the box HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord® Dimensions (Lx Wx H) 50.42 x 5.08 x 30.3 cm Weight 2.8 kg Package Dimensions (Lx Wx H) 56.7 x 12.1 x 38.7 cm Package weight 4.3 kg Pallet (layers) 6 Products per layer 16 Products per pallet 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm		
Port and Connectors 1 VGA; 1 HDMI 1.4 HDCP Ves, HDMI Management software HP Display Center ¹¹ Warranty 1 year limited warranty Certifications and compliances Bauart; TUV EBL; VCC; VCE; VCEP, CEL; CSA; EAC; ENERGY STAR®, FCC; ISO 9241-307; KC/KIC; Microsoft WHQL Certification; NOM; PSR; RoHS; SEPA; TCO Certified; TCO Certified Edge; TUV Bauart; TUV EBL; VCC; VCE; VCEP, CEL; CSA; EAC; ENERGY STAR®, FCC; ISO 9241-307; KC/KIC; Microsoft WHQL Certification; NOM; PSR; RoHS; SEPA; TCO Certified; TCO Certified Edge; TUV Bauart; TUV EBL; VCC; VCEP, VCEP, CEL; CSA; EAC; ENERGY STAR®, FCC; ISO 9241-307; KC/KIC; Microsoft WHQL Certification; NOM; PSR; RoHS; SEPA; TCO Certified; TCO Certified Edge; TUV Bauart; TUV EBL; VCC; VCEP, VCEP, CEL; CSA; EAC; ENERGY STAR®, FCC; ISO 9241-307; KC/KIC; Microsoft WHQL Certification; NOM; PSR; RoHS; SEPA; TCO Certified;		
HDCP Yes, HDMI Management software HP Display Center ¹¹ Warranty 1 year limited warranty Certifications and compliances Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; CSA; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC, Microsoft WHQL Certification; NOM; PSB; RoHS; SEPA; TCO Certified Edge; TUV Bauart; TUV LBL; VCCI; Vietnam MEPS; WEEE; ISC; China Energy Label (CEL) Grade 2; California Energy Commission (CEC); WW application; ICE; UAE; Ukraine certificates; TUV Flicker free certified What's in the box HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord ⁹ Dimensions (L x W x H) 50.42 x 5.08 x 30.3 cm Weight 2.8 kg Package Dimensions (L x W x H) 56.7 x 12.1 x 38.7 cm Package weight 4.3 kg Pallet (Jayers) 6 Products per Jayer 16 Products per Jayer 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm		
Management software HP Display Center ¹¹ Warranty 1 year limited warranty Certifications and compliances Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; CSA; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; Microsoft WHQL Certification; NOM; PSB; RoHS; SEPA; TCO Certified Edge; TUV Bauart; TUV LBL; VCC; Vietnam MEPS; WEEE; ISC; China Energy Label (CEL) Grade 2; California Energy Commission (CEC); WW application; ICE; UAE; Ukraine certificates; TUV Flicker free certified What's in the box HDMI cable; Warranty card; Quick Setup Poster; Doc-klt; AC power cord ⁹ Dimensions (L x W x H) 50.42 x 5.08 x 30.3 cm Weight 2.8 kg Package Dimensions (L x W x H) 56.7 x 12.1 x 38.7 cm Package weight 4.3 kg Pallet (Jayers) 6 Products per Jayer 16 Products per Jayer 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm		
Waranty 1 year limited warranty Certifications and compliances Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; CSA; EAC; ENERGY STAR®; F.CC; ISO 9241-307; KC/KCC; Microsoft WHQL Certification; NOM; PSB; RoHS; SEPA; TCO Certified Edge; TUV Bauart; TUV LBI; VCC; Vietnam MEPS; WEEE; ISC; China Energy Label (CEL) Grade 2; California Energy Commission (CEC); WW application; ICE; UAE; Ukraine certificates; TUV Flicker free certified What's in the box HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord ⁹ Dimensions (L x W x H) 50.42 x 5.08 x 30.3 cm Weight 2.8 kg Package Dimensions (L x W x H) 56.7 x 12.1 x 38.7 cm Package weight 4.3 kg Pallet (Jayers) 6 Products per Jayer 16 Products per Jayer 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm	•	
Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; CSA; EAC; ENERGY STAR®; FCC; ISO 9241-307; KC/KCC; Microsoft WHQL Certification; NOM; PSB; RoHS; SEPA; TCO Certified Edge; TUV Blauri; TUV IBI; VCC; Vietnam MEPS; WEEE; ISC; China Energy Label (CEL) Grade 2; California Energy Commission (CEC); WW application; ICE; UAE; Ukraine certificates; TUV Flicker free certified What's in the box HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord ⁹ Dimensions (L x W x H) 50.42 x 5.08 x 30.3 cm Weight 2.8 kg Package Dimensions (L x W x H) 56.7 x 12.1 x 38.7 cm Package weight 4.3 kg Pallet (Jayers) 6 Products per layer 16 Products per pallet 96 Products per pallet 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm		
Bauart, TUV.BI; VCCI; Vietnam MEPS; WEEE; ISC; China Energy Label (CEL) Grade 2; California Energy Commission (CEC); WW application; ICE; UAE; Ukraine certificates; TÜV Flicker free certified What's in the box HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord ⁹ Dimensions (Lx Wx H) 50.42 x 5.08 x 30.3 cm Weight 2.8 kg Package Dimensions (Lx Wx H) 56.7 x 12.1 x 38.7 cm Package weight 4.3 kg Pallet (Jayers) 6 Products per Jayer 16 Products per pallet 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm	Warranty	
Dimensions (LxWxH) 50.42 x 5.08 x 30.3 cm Weight 2.8 kg Package Dimensions (LxWxH) 56.7 x 12.1 x 38.7 cm Package weight 4.3 kg Pallet (layers) 6 Products per layer 16 Products per pallet 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm	Certifications and compliances	
Weight 2.8 kg Package Dimensions (L x W x H) 56.7 x 12.1 x 38.7 cm Package weight 4.3 kg Pallet (layers) 6 Products per layer 16 Products per pallet 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm	What's in the box	HDMI cable; Warranty card; Quick Setup Poster; Doc-kit; AC power cord ⁹
Package Dimensions (LxWxH) 56.7 x 12.1 x 38.7 cm Package weight 4.3 kg Pallet (layers) 6 Products per layer 16 Products per pallet 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm	Dimensions (L x W x H)	50.42 x 5.08 x 30.3 cm
Package weight 4.3 kg Pallet (layers) 6 Products per layer 16 Products per pallet 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm	Weight	2.8 kg
Pallet (layers) 6 Products per layer 16 Products per pallet 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm	Package Dimensions (L x W x H)	56.7 x 12.1 x 38.7 cm
Products per layer 16 Products per pallet 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm	Package weight	4.3 kg
Products per pallet 96 Pallet dimensions 96.8 x 113.4 x 206.3 cm	Pallet (layers)	6
Pallet dimensions 96.8 x 113.4 x 206.3 cm	Products per layer	16
	Products per pallet	96
Pallet weight 362.41 kg	Pallet dimensions	96.8 x 113.4 x 206.3 cm
	Pallet weight	362.41 kg

Messaging Footnotes

- ¹ All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower. ² Host PC requires Windows 10 or higher. HP Display Center is available on the Microsoft store.
- ³ Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit www.epeat.net for more information. ⁴ ITE Derived Closed Loop Plastic percentage is based on the definition set in the IEEE 1680.1-2018 standard.
- 5 100% outer box/corrugate cushion packaging made from sustainably sourced certified and recycled fibers. Fiber cushions made from 100% recycled wood fiber and organic material. Any plastic cushions are made from >90% recycled plastic. Excludes plastic bags and plastic foam sheeting

Technical Specifications Footnotes

- 1 All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower
- ² HDMI 1.4 or VGA required to drive panel at its native resolution. The video card of the connected PC must be capable of supporting 1920 x 1080 at 60 Hz with 8-bit color using one HDMI, VGA. The video card of the connected PC must be acapable of supporting 1920 x 1080 and include one HDMI or one VGA outputs to drive the monitor at the Preferred Mode.

 Number of colors through A-FRC technology.

 EPEAT® registered where applicable. EPEAT® registration varies by country. See www.epeat.net for registration status by country. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit www.epeat.net for more information.

- Securified plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.

 Molded pulp cushions are made from 100% recycled wood fiber and organic materials.

 External power supplies, WWAN modules, power cords, cables and peripherals excluded. Service parts obtained after purchase may not be Low Halogen.
- $^{\rm 8}$ ITE Derived Closed Loop Plastic percentage is based on the definition set in the IEEE 1680.1–2018 standard. $^{\rm 9}$ Included cables may vary by country.
- 10 Lock sold separately.
- 11 HP Display Center requires Windows 10 (or higher) on host PC and is available from the Windows store 12 Mounting hardware sold separately.

