

Optix G241VC





SPECIFICATIONS

VESA Mounting 75 x 75 mm, 100 x 100mm) (sold separately) Control Menu, Bri (-), Vol(+) Input/Enter, Power Power Type Internal Adaptor Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch	Panel Size	23.6" (60cm)
Panel Type VA Brightness (nits) 250 nits Viewing Angle 178° (H) / 178° (V) Aspect Ratio 16:9 Curvature 1800R Contrast Ratio 3000:1 Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1x HDMI™ (1.4) 1x VGA Requires special MSI wall mount adaptor 75 x 75 mm, 100 x 100mm) (sold separately) Control Menu, Bri (-), Vol(+) Input/Enter, Power Power Type Internal Adaptor Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch Weight (NW / GW) 4.1kg / 5.5kg	Panel Resolution	1920 x 1080 (FHD)
Section Sec	Refresh Rate	75Hz
Viewing Angle 178° (H) / 178° (V) Aspect Ratio 16:9 Curvature 1800R Contrast Ratio 3000:1 Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1x HDMI™ (1.4) 1x VGA Requires special MSI wall mount adaptor 75 x 75 mm, 100 x 100mm) (sold separately) Control Menu, Bri (-), Vol(+) Input/Enter, Power Power Type Internal Adaptor Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW) 4.1kg / 5.5kg	Panel Type	VA
Aspect Ratio 16:9 Curvature 1800R Contrast Ratio 3000:1 Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1x HDMI™ (1.4) 1x VGA Requires special MSI wall mount adaptor VESA Mounting Requires special MSI wall mount adaptor 75 x 75 mm, 100 x 100mm) (sold separately) Control Menu, Bri (-), Vol(+) Input/Enter, Power Power Type Internal Adaptor Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch Carton Dimension (W X H X D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch	Brightness (nits)	250 nits
Curvature 1800R Contrast Ratio 3000:1 Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1x HDMI™ (1.4) 1x VGA Requires special MSI wall mount adaptor 75 x 75 mm, 100 x 100mm) (sold separately) Control Menu, Bri (-), Vol(+) Input/Enter, Power Power Type Internal Adaptor Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch Carton Dimension (W X H X D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	Viewing Angle	178° (H) / 178° (V)
Contrast Ratio 3000:1 Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1x HDMI™ (1.4) 1x VGA Requires special MSI wall mount adaptor 75 x 75 mm, 100 x 100mm) (sold separately) Separately) Control Menu, Bri (-), Vol(+) Input/Enter, Power Power Type Internal Adaptor Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	Aspect Ratio	16:9
Active Display Area (mm) Pixel Pitch (H x V) Surface Treatment Display Colors 16.7M Video ports 1x HDMI™ (1.4) 1x VGA Requires special MSI wall mount adaptor 75 x 75 mm, 100 x 100mm) (sold separately) Control Power Type Internal Adaptor Power Input 100~240V, 50~60Hz DCR NTSC / sRGB 85% / 115% Power consumption Signal Frequency Adjustment (Tilt) Dimension (W x H x D) Carton Dimension (W X H X D) S12.3952(H) x 293.2848(V) 0.27156(H) x 0.27156(V) Anti-glare 14.14 Anti-glare 14.1	Curvature	1800R
Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1x HDMI™ (1.4) 1x VGA Requires special MSI wall mount adaptor 75 x 75 mm, 100 x 100mm) (sold separately) Control Menu, Bri (-), Vol(+) Input/Enter, Power Power Type Internal Adaptor Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch Carton Dimension (W X H X D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	Contrast Ratio	3000:1
Surface TreatmentAnti-glareDisplay Colors16.7MVideo ports1x HDMI™ (1.4) 1x VGAVESA MountingRequires special MSI wall mount adaptor 75 x 75 mm, 100 x 100mm) (sold separately)ControlMenu, Bri (-), Vol(+) Input/Enter, PowerPower TypeInternal AdaptorPower Input100~240V, 50~60HzDCR100000000:1NTSC / sRGB85% / 115%Power consumption45WSignal Frequency54.2 to 84.3KHz (H) 48 to 75Hz (V)Adjustment (Tilt)-5° ~ 15°Dimension (W x H x D)543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inchCarton Dimension (W X H X D)621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inchWeight (NW / GW)4.1kg / 5.5kg	Active Display Area (mm)	521.3952(H) x 293.2848(V)
Display Colors 16.7M Video ports 1x HDMI™ (1.4) 1x VGA Requires special MSI wall mount adaptor 75 x 75 mm, 100 x 100mm) (sold separately) Control Menu, Bri (-), Vol(+) Input/Enter, Power Power Type Internal Adaptor Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch Carton Dimension (W X H X D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	Pixel Pitch (H x V)	0.27156(H) x 0.27156(V)
Video ports 1x HDMI™ (1.4) 1x VGA VESA Mounting Requires special MSI wall mount adaptor 75 x 75 mm, 100 x 100mm) (sold separately) Control Menu, Bri (-), Vol(+) Input/Enter, Power Internal Adaptor Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch Carton Dimension (W X H X D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	Surface Treatment	Anti-glare
VESA Mounting 1x VGA Requires special MSI wall mount adaptor 75 x 75 mm, 100 x 100mm) (sold separately) Control Menu, Bri (-), Vol(+) Input/Enter, Power Power Type Internal Adaptor Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch Carton Dimension (W X H X D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	Display Colors	16.7M
VESA Mounting 75 x 75 mm, 100 x 100mm) (sold separately) Control Menu, Bri (-), Vol(+) Input/Enter, Power Power Type Internal Adaptor Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch Carton Dimension (W X H X D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	Video ports	• •
Power Type Internal Adaptor Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch Carton Dimension (W X H X D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	VESA Mounting	
Power Input 100~240V, 50~60Hz DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.59 inch Carton Dimension (W X H X D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	Control	Menu, Bri (-), Vol(+) Input/Enter, Power
DCR 100000000:1 NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.59 inch Carton Dimension (W X H X D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	Power Type	Internal Adaptor
NTSC / sRGB 85% / 115% Power consumption 45W Signal Frequency 54.2 to 84.3 KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch Carton Dimension (W X H X D) inch 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	Power Input	100~240V, 50~60Hz
Power consumption 45W Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch Carton Dimension (W X H X D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	DCR	100000000:1
Signal Frequency 54.2 to 84.3KHz (H) 48 to 75Hz (V) Adjustment (Tilt) -5° ~ 15° Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch Carton Dimension (W X H X D) 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	NTSC / sRGB	85% / 115%
Adjustment (Tilt) -5° ~ 15°	Power consumption	45W
Dimension (W x H x D) 543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch Weight (NW / GW) 4.1kg / 5.5kg	Signal Frequency	, ,
Carton Dimension (W X H X D) inch 621 x 421 x 148 mm / 24.4 x 16357 x 5.8 inch 4.1kg / 5.5kg	Adjustment (Tilt)	-5° ~ 15°
Weight (NW / GW) inch 4.1kg / 5.5kg	Dimension (W x H x D)	543 x 403 x 192 mm / 21.3 x 15.86 x 7.55 inch
	Carton Dimension (W X H X D)	621 x 421 x 148 mm / 24.4 x 16357 x 5.82 inch
	Weight (NW / GW)	
Frameless Design Yes	Frameless Design	Yes
Note VGA: 1920 x 1080 (Up to 75Hz) HDMI™: 1920 x 1080 (Up to 75Hz) The color gamut follows the CIE 1976 testing standard.	Note	HDMI™: 1920 x 1080 (Up to 75Hz) The color gamut follows the CIE 1976 testing

FEATURES




Curved Gaming™



View more of your game. MSI Curved Gaming[™] monitors are perfect for gamers to play their games.



Curved Gaming





1ms Fast Response Time Eliminate screen tearing and choppy frame rates with 1ms $\,$ response time.



Wide Color Gamut

wide Color Game colors and details will look more realistic and refined, to IGAMUTE push game immersion to its limits.



75Hz High Refresh Rate

75 Hz Experience smooth gaming with a blazing fast 75Hz refresh rate, that gives you the upperhand in fast moving games.



FreeSync technology

AMD FreeSync® will prevend screen tearing or stuttering, producing ultra-smooth and lag-free gameplay.



Game Mode

Enable a monitor crosshair overlay to help get the best aim in games that may have small or no crosshair at all.



MONITOR Optix G241VC

CONNECTIONS



- 1. 1x Power Plug
- 2. 1x VGA
- 3. 1x HDMI[™] (1.4)