

Philips Monitor UltraWide LCD monitor

E Line 34" (86.36 cm) 3440 x 1440 (WQHD)

346E2LAE

Simplify your connections with USB-C

The Philips E line UltraWide display offers expansive panoramic visuals. The WQHD display and ergonomic stand guarantee the optimal viewing conditions. Features like allin-one USB-C, built-in USB Hub and MultiView help boost up productivity.

Single cable USB-C connection

• Connect your notebook with one USB-C cable

Superb Picture Quality

- · VA display delivers awesome images with wide viewing angles
- CrystalClear images with UltraWide QHD 3440 x 1440 pixels

Good for Gaming

- 1 ms (MPRT) fast response for crisp images and smooth gameplay
- · SmartImage game mode optimised for gamers

Features designed for you

- · Less eye fatigue with Flicker-Free technology
- · LowBlue Mode for easy-on-the-eyes productivity
- · MultiView enables simultaneous dual connection and view
- · Built-in stereo speakers for multimedia
- Cable management reduces cable clutter for a neat workspace
- · Tilt and height-adjust for an ideal viewing position



UltraWide LCD monitor E Line 34" (86.36 cm), 3440 x 1440 (WQHD)


Highlights

USB-C connection



This Philips display features a USB type-C connector with power delivery. With intelligent and flexible power management, you can power charge your compatible device directly. Its slim, reversible USB-C allows for easy, one-cable connection. You can watch high-resolution video and transfer data at super speed, while powering up and recharging your compatible device at the same time.

VA display



The Philips VA LED display uses an advanced multi-domain vertical alignment technology that gives you super-high static contrast ratios for extra-vivid and bright images. While standard office applications are handled with ease, it is especially suitable for photos, web browsing, films, gaming and demanding graphical applications. Its optimised pixel management technology gives you a 178/178 degree extra-wide viewing angle, resulting in crisp images.

UltraWide CrystalClear images



These Philips screens deliver Crystal Clear, UltraWide Quad HD 3440 x 1440 pixel images. Utilising high-performance panels with high-density pixel count and 178/178 wide viewing angles, these new displays will make your images and graphics come alive. The UltraWide 21:9 format enables more productivity with more room for side-by-side comparisons and more viewable spreadsheet columns. Whether you are a demanding professional requiring extremely detailed information for CAD-CAM solutions or a financial wizard working on huge spreadsheets, Philips displays deliver Crystal Clear images.

1 ms MPRT fast response



MPRT (motion picture response time) is a more intuitive way to describe response time, which directly refers to the duration between seeing blurry noise and clean, crisp images. The Philips gaming monitor with 1 ms MPRT effectively eliminates smearing and motion blur and delivers sharper and more precise visuals to enhance your gaming experience. The best choice for playing thrilling and twitch-sensitive games.

SmartImage Game mode



The new Philips gaming display has quickaccess OSD fine-tuned for gamers, offering you multiple options. "FPS" mode (First person shooting) improves dark themes in games, allowing you to see hidden objects in dark areas. "Racing" mode adapts the display with the fastest response time and high colour, along with image adjustments. "RTS" mode (Real-time strategy) has a special SmartFrame mode that enables highlighting of specific area and allows for size and image adjustments. Gamer 1 and Gamer 2 enable you to save personal customised settings based on different games, ensuring best performance.

Flicker-Free technology



Due to the way brightness is controlled on LED-backlit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-Free technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.



























Specifications

Picture/Display

- LCD panel type: VA LCD
- Backlight type: W-LED system
- Panel Size: 34 inch / 86.36 cm
- Display Screen Coating: Anti-Glare, 3H, Haze 25%
 Effective viewing area: 797.22 (H) x 333.72 (V) mm
- Aspect ratio: 21:9
- Maximum resolution: 3440 x 1440 @ 100 Hz*
- Pixel Density: 109.68 PPI
- Response time (typical): 4 ms (Gray to Gray)*
- MPRT: 1 ms
- Brightness: 300 cd/m²
- Contrast ratio (typical): 4000:1
- SmartContrast: Mega Infinity DCR
- Pixel pitch: 0.23175 x 0.23175 mm
 Viewing angle: 178° (H)/178° (V), @ C/R > 10
- Flicker-free
- Picture enhancement: SmartImage game
- Colour gamut (typical): NTSC 100.05%*, sRGB
- 121.32% • Display colours: 16.7 M (8 bit)
- Scanning Frequency: 30–160 kHz (H)/48–100 Hz (V)
- LowBlue Mode
- EasyRead
- sRGB
- Adaptive sync

Connectivity

- Signal Input: HDMI 2.0 x 1, DisplayPort 1.2 x 1, USB-C x 1 (DP Alt mode, Power delivery)
- HDCP: HDCP 1.4 (HDMI/DisplayPort/USB-C), HDCP 2.2 (HDMI/DisplayPort/USB-C)
- USB Hub: USB 3.2 Gen 1 / 5 Gbps, USB-A downstream x 4 (with 1 fast charge B.C 1.2)
- Audio (In/Out): Audio out
- Sync Input: Separate Sync

Power Delivery

- Version: USB PD version 3.0
- Max power delivery: USB-C up to 65 W (5 V/3 A, 7 V/3 A, 9 V/3 A, 10 V/3 A, 12 V/3 A, 15 V/3 A, 20 V/3.25 A)

Convenience

- Built-in Speakers: 3 W x 2
- MultiView: PIP/PBP mode, 2 x devices
- User convenience: Power On/Off, Menu, Volume,
- Input, SmartImage Game OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
- Other convenience: Kensington lock, VESA mount

- (100 x 100 mm)
- Plug and Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 11 / 10 / 8.1 / 8 / 7

Stand

- Height adjustment: 100 mm
- Tilt: -5/20 degree

Power

- On mode: 35 W (typ.)
 Standby mode: 0.5 W (typ.)
- Off mode: 0.3 W (typ.)
- · Energy Label Class: F
- · Power LED indicator: Operation White, Standby mode - White (flashing)
- Power supply: External, 100-240 VAC, 50-60 Hz

Dimensions

- Product with stand (max height): 817 x 491 x
 - 235 mm
- Product without stand (mm): 817 x 365 x 49 mm
- Packaging in mm (W x H x D): $930 \times 525 \times 186$ mm

Weight

- Product with stand (kg): 7.36 kg
- Product without stand (kg): 5.43 kg
- Product with packaging (kg): 10.70 kg

Operating conditions

- Temperature range (operation): 0 to 40 °C
- Temperature range (storage): -20 to 60 °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000 ft (3658 m), Nonoperation: +40,000 ft (12,192 m) • MTBF: 50,000 hrs (excluding backlight) hour(s)

Sustainability

- Environmental and energy: RoHS
- Recyclable packaging material: 100 %
- Specific Substances: Mercury free, PVC/BFR free housing

Compliance and standards

• Regulatory Approvals: CB, TUV/ISO9241-307, TUV-BAUART, CU-EAC, EAEU RoHS, CE Mark, FCC Class B, ICES-003

Cabinet

 Colour: Black Finish: Textured

- What's in the box? · Monitor with stand
- Cables: HDMI cable, USB-C to USB-C cable,
- Power cable
- User Documentation

- ⁴ The maximum resolution works for either HDMI input or DP input.
- * For best output performance, please always ensure that your gra card is capable of achieving the maximum resolution and refresh rate of this Philips display.
- Response time value equal to SmartResponse
- * MPRT adjusts the brightness for blur reduction, so the brightness cannot be adjusted while MPRT is turned on. To reduce motion blur, the LED backlight will strobe in time with the screen refresh rate, which may cause a noticeable change in brightness.
- * MPRT is a gaming-optimised mode. Turning on MPRT may cause noticeable screen flickering. It is recommended to turn this mode off
- when you are not using the gaming function. * NTSC Area based on CIE 1976

46E2LAE/01

- * sRGB Area based on CIE1931 * For USB-C power and charging function, your Notebook/device must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more details
- ^k For Video transmission via USB-C, your Notebook/device must support USB-C DP Alt mod
- * The monitor may look different from feature images.



Issue date 2022-09-01 Version: 1.1.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 85109 EAN: 87 12581 79614 3 © 2022 Koninklijke Philips N.V. All Rights reserved.

www.philips.com