

Philips

LCD monitor with SmartImage lite

- Ultra-Narrow Bezel
- 21.5"/54.6 cm
- MHL

224E5ODAB/00

Vibrant images with AH-IPS display

with Ultra-Narrow Bezel, MHL

This attractive Philips display with ultra-narrow bezel and AH-IPS screen gives you awesome, vibrant colour images. Mobile HD link allows you to connect your Smartphone.

Benefits

Entertainment with Mobile HD Link (MHL)

- MHL technology for enjoying mobile content on a big screen
- HDMI-ready for Full HD entertainment
- Superb 10 watts stereo sound
- · Charge your mobile device while watching a movie
- Optional MHL cable allows for HD video audio playback

Awesome picture quality

- AH-IPS display gives awesome images with wide viewing angles
- 16:9 Full HD display for the best viewing experience

- TrueVision ensures lab quality images
- SmartImage Lite for an enhanced LCD viewing experience

Stylish design

- Minimalistic looks with Ultra-Narrow Bezel
- Superb glossy and textured finish
- VESA mount for convenience



Features

MHL technology



Mobile High-Definition Link (MHL) is a mobile audio/video interface for directly connecting mobile phones and other portable devices to highdefinition displays. An optional MHL cable allows you to simply connect your MHL-capable mobile device to this large Philips MHL display and watch your HD videos come to life with full digital sound. Now not only can you enjoy your mobile games, photos, movies or other apps on its big screen, you can simultaneously charge your mobile device so you never run out of power halfway.

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input, high quality digital video and audio signals all transmitted over a single cable from a PC or any number of AV sources including set-top boxes, DVD players and A/V receivers and video cameras.

Superb 10 watts stereo sound

A pair of high-quality stereo speakers built into a display device. They may be visible front firing, or invisible down firing, top firing, rear firing etc. depending on model and design.

AH-IPS technology



IPS displays use an advanced technology that gives you extra-wide viewing angles of 178/178 degrees, making it possible to view the display from almost any angle. Unlike standard TN panels, IPS displays give you remarkably crisp images with vivid colours, making them ideal not only for Photos, movies and web browsing, but also for professional applications that demand colour accuracy and consistent brightness at all times.

16:9 Full HD



The Full HD screen has the widescreen resolution of 1920 x 1080p. This is the highest resolution of HD sources for the best possible picture quality. It is fully future-proof as it supports 1080p signals from all sources, including the most recent sources such as Blu-ray and advanced HD game consoles. The signal processing is extensively upgraded to support this much higher signal quality and resolution. It produces brilliant flicker-free progressive scan pictures with superb brightness and colours.

TrueVision





TrueVision is a proprietary Philips technology that uses an advanced algorithm for testing and aligning monitor display, which gives you the ultimate display performance. Philips ensures that TrueVision monitors leave the factory finetuned with this process giving you consistent colour and picture quality.

SmartImage Lite

SmartImage Lite is an exclusive, leading edge Philips technology that analyses the content displayed on your screen. Based on a scenario you select, SmartImage Lite dynamically enhances the contrast, colour saturation and sharpness of images and videos for ultimate display performance - all in real time with the press of a single button.

Ultra-Narrow Bezel

Utilising the latest technology panels, the new Philips displays are designed with a minimalistic approach by limiting the outer bezel thickness to about 2.5 mm. Combined with an in-panel black matrix strip of around 9 mm, the overall bezel dimensions are reduced significantly, minimising distractions and maximising viewing size. Especially suited to multi-display or tiling setups like gaming, graphics design and professional applications, the Ultra-narrow bezel display gives you the feeling of using one large display.

Specifications

Please note that this is a pre-sales leaflet. The contents of this leaflet reflect the best of our knowledge per date and country mentioned above. The contents of this leaflet are subject to change without notice. Philips does not accept any liability as to the contents of this leaflet.

Picture/Display

LCD panel type AH-IPS LCD Backlight type W-I FD system Panel Size 21.5 inch/54.6 cm Effective viewing area 476.1 (H) x 267.8 (V) Aspect ratio Sync Input Optimum resolution 1920 x 1080 @ 60 Hz SmartResponse 5 ms (Grey to Grey) Audio (In/Out) (typical) 250 cd/m² **Brightness** Contrast ratio 1000:1 (typical) 20,000,000:1 SmartContrast Pixel pitch 0.248 x 0.248 mm 178° (H)/178° (V) Viewing angle

@ C/R > 10 Picture enhancement SmartImage Lite

Display colours 16.7 M Scanning Frequency 30-83 kHz (H)/56-75 Hz (V)

1080p@30Hz sRGB Yes

MHL

Connectivity

MHL-HDMI (digital, HDCP) Signal Input

VGA (Analogue)

DVI-D (digital, HDCP)

Separate Sync Sync on Green

PC audio-in

Headphone out

Convenience

Built-in Speakers 5 watts x 2 User convenience Power On/Off

Menu Volume Input

SmartImage lite **Brazil Portuguese** OSD Languages

Czech Dutch

> data subject to change 2015, February 19

English Finnish French German Greek Hungarian Italian Japanese Korean Polish Portuguese Russian Simplified Chinese

Spanish Swedish

Traditional Chinese

Turkish Ukrainian Kensington lock

DDC/CI

Other convenience VESA mount (100 x 100 mm)

Plug and Play Compatibility

Mac OS X sRGB Windows 7 Windows 8

Stand

Tilt -5/20 degree

Power

On mode 17.46 W (typ.) (EnergyStar 6.0 test

method)

Standby mode 0.5 W (typ.) 0.3 W (typ.) Operation - White Off mode Power LED indicator

Standby mode - White (flashing)

Power supply External

100-240 VAC, 50-60 Hz

Dimensions

Product with stand 500 x 394 x 213 mm (mm)

Product without

stand (mm)

Packaging in mm (W

x H x D

 $500 \times 306 \times 47 \text{ mm}$ 562 x 466 x 106 mm

Product with stand 3.14 kg

(kg)

Weight

Product without 2.82 kg

stand (kg)

Product with pack-5.01 kg aging (kg)

Operating conditions

Temperature range (operation)

Temperature range

(storage)

Relative humidity 20-80% %

Operation: +12,000 ft (3658 m), Non-Altitude

0°C to 40°C °C

-20°C to 60°C °C

operation: +40,000 ft (12,192 m)

MTBF 30,000 hour(s)

Sustainability

Environmental and

energy

EnergyStar 6.0 EPEAT Silver RoHS Lead-free

Mercury Free Recyclable packaging 100 %

material

Compliance and standards

Regulatory Approvals **BSMI**

CE Mark FCC Class B GOST SASO SEMKO TCO 6.0

TUV/ISO9241-307

WEEE

Cabinet

Colour Black Cherry/Black

Finish Glossy

^{*} Smart response time is the optimum value from either GtG or GtG (BW) tests.



data subject to change 2015, February 19

Version: 2.0.1 EAN: 8712581704988 © 2015 Koninklijke Philips Electronics N.V.

All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

^{*} This Philips display is MHL-certified. However, if your MHL device does not connect or work correctly, check with your MHL device FAQ or vendor directly for instructions. The policy of your device manufacturer may require you to purchase its brand-specific MHL cable or adapter in order for it to work

^{*} Requires optional MHL-certified mobile device and MHL cable (not included). Please check with your MHL device vendor for compatibility.

^{*} Standby/Off energy saving of ErP is not applicable for the MHL charging functionality

^{* &}quot;IPS" word mark / trademark and related patents on technologies belong to their respective owners.