

LCD monitor with SmartControl Lite

• V Line • 23.6" / 59.9 cm

243V5LSB/27

Great LED images in vivid colors

Enjoy vivid LED pictures on this Philips display. Equipped with SmartControl lite, it's a great choice!

Benefits

Vivid pictures every time

- LED technology for vivid colors
- Easy display performance tuning with SmartControl Lite
- SmartContrast for rich black details
- 16:9 Full HD display for best viewing experience

Features

LED technology

White LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of LCD backlight, resulting in super high contrast ratio. It also gives superior color reproduction thanks to consistent brightness across the screen.

Great choice

- Mercury Free eco-friendly display
- Compact design saves space
- · VESA mount allows for flexibility

SmartControl Lite

SmartControl Lite is the next generation 3D icon based GUI monitor control software. This allows user to fine-tune most parameters of the monitor like Color, Brightness, screen calibration, Multi-media, ID management, etc with the mouse.



SmartContrast



SmartContrast is a Philips technology that analyzes the contents you are displaying, automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

16:9 Full HD



The Full HD screen has the widescreen resolution of 1920 x 1080p. This is the highest resolution of HD sources for the best possible picture quality. It is fully future proof as it supports 1080p signals from all sources, including the most recent like Blu-ray and advanced HD game consoles. The signal processing is extensively upgraded to support this much higher signal quality and resolution. It produces brilliant flicker-free progressive scan pictures with superb brightness and colors.

TFT-LCD

16:9

5 ms

250 cd/m²

1000:1

16.7 M

Yes

10,000,000:1

@ C/R > 10

0.272 x 0.272 mm

170° (H) / 160° (V)

30 -83 kHz (H) / 56 -75 Hz (V)

W-LED system

23.6 inch / 59.9 cm

521.28 (H) x 293.22 (V)

1920 x 1080 @ 60 Hz

Specifications

Please note that this is a pre-sales leaflet. The contents of this leaflet reflect the best of our knowledge per date and country mentioned above. The contents of this leaflet are subject to change without notice. Philips does not accept any liability as to the contents of this leaflet.

Picture/Display

LCD panel type Backlight type Panel Size Effective viewing area Aspect ratio Optimum resolution Response time (typical) Brightness SmartContrastContrast ratio (typical) Pixel pitch Viewing angle

Display colors Scanning Frequency sRGB

Connectivity

Signal Inp

Sync Input

VGA (Analog) DVI-D (digital, HDCP) Separate Sync Sync on Green

Convenience

User convenience

OSD Languages

Brightness/Back Menu/OK Power On/Off Brazil Portuguese Czech Dutch English

Auto/Down

4:3 Wide/Up

Mercury Free

Philips monitors with LED backlighting are free of Mercury content, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its life-cycle, from manufacturing to disposal.

Korean Polish Portuguese Russian Spanish Swedish Turkish Ukranian Other convenience DDC/CI Plug & Play Compati-Mac OS X sRGB Windows 7

Finnish

French

Greek

ltalian

Japanese

German

Hungarian

Simplified Chinese Traditional Chinese Kensington lock VESA mount (100x100mm) Windows 8

-5/20 degree

Stand

Tilt

bility

Power On mode

Standby mode Off mode Power LED indicator

Power supply

16.7 W (typ.) (EnergyStar 6.0 test method) 0.5 W (typ.) 0.5 W (typ.) Operation - White Standby mode- White (blinking) Built-in

> data subject to change 2017, November 8

Dimensions	
Product with stand	551 x 420 x 220 mm
(mm) Product with stand in	21.7 x 16.5 x 8.7 inch
inch	21.7 × 10.5 × 0.7 men
Product without	551 x 344 x 52 mm
stand (mm)	24 7 42 5 20 1
Product without stand in inch	21.7 x 13.5 x 2.0 inch
Packaging in mm	600 x 415 x 118 mm
(WxHxD)	
Packaging in inch	23.6 x 16.3 x 4.6 inch
(WxHxD)	

100-240VAC, 50-60Hz

Weight

Product with stand	3.66 kg
(kg)	
Product with stand	8.05 lb
(lb)	
Product without	3.22 kg
stand (kg)	
Product without	7.08 lb
stand (lb)	
Product with pack-	5.00 kg
aging (kg)	
Product with pack-	11.00 lb
aging (lb)	

Operating conditions

Temperature range	0°C to 40°C °C
(operation) Temperature range (storage)	-20°C to 60°C °C

Relative humidity Altitude

MTBF

Sustainability

Environmental and

energy

EnergyStar 6.0 EPEAT Silver RoHS Lead-free Mercury Free 100 %

20%-80 %

Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)

50,000 (Excluded backlight) hour(s)

Recyclable packaging material

Compliance and standards Regulatory Approvals

BSMI CE Mark cETLus FCC Class B GOST PSB SASO SEMKO TCO certified TUV/ISO9241-307 WEEE

Cabinet

Color Finish Black Hairline (front bezel) / Texture (rear cover)



data subject to change 2017, November 8

Version: 2.0.1 UPC: 609585248663 © 2017 Koninklijke Philips N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com