

LCD monitor

- S Line
- 24 (23.6"/59.9 cm diag.)
- Full HD (1920 x 1080)

243S5LSB5/00

Essential features, efficient performance

for maximum productivity

The Philips LED display using PVC, BFR-free housing is ideal for eco-friendly productivity

Benefits

Vivid pictures every time

- · LED technology for vivid colours
- SmartContrast for rich black details
- 16:9 Full HD display for crisp, detailed images
- Great choice

Features

LED technology

White LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content, which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of the LCD backlight, resulting in a super high contrast ratio. It also gives superior colour reproduction thanks to consistent brightness across the screen.

- Mercury Free eco-friendly display
- · Compact design saves space
- VESA mount allows for flexibility



SmartContrast



SmartContrast is a Philips technology that analyses the contents you are displaying, automatically adjusting colours and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

16:9 Full HD display



Picture quality matters. Regular displays deliver quality, but you expect more. This display features enhanced Full HD 1920 \times 1080 resolution. With Full HD for crisp detail paired with high brightness, incredible contrast and realistic colours, expect a true-to-life picture.

Specifications

Please note that this is a pre-sales leaflet. The contents of this leaflet reflect the best of our knowledge per date and country mentioned above. The contents of this leaflet are subject to change without notice. Philips does not accept any liability as to the contents of this leaflet.

Picture/Display

LCD panel type TFT-LCD Backlight type W-LED system Panel Size 23.6 inch/59.9 cm Effective viewing area 521.28 (H) x 293.22 (V)

Aspect ratio

1920 x 1080 @ 60 Hz Optimum resolution

Pixel Density 93 PPI Response time 5 ms

(typical)

Brightness 250 cd/m² 10,000,000:1 SmartContrast 1000:1 Contrast ratio

(typical)

Pixel pitch 0.272 x 0.272 mm 170° (H)/160° (V) Viewing angle @ C/R > 10

Display colours 16.7 M

30-83 kHz (H) / 56-76 Hz (V) Scanning Frequency

sRGB

Connectivity

Signal Input VGA (Analogue) DVI-D (digital, HDCP) Sync Input Separate Sync

Sync on Green

Convenience

User convenience Power On/Off Menu/OK

Brightness/Back 4:3 Wide/Up Auto/Down

OSD Languages **Brazil Portuguese**

> Dutch English Finnish French

Czech

Mercury Free

Philips monitors with LED backlighting are free from Mercury, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its lifecycle, from manufacturing to disposal.

> German Greek Hungarian Italian Japanese Korean Polish Portuguese Russian Spanish

Simplified Chinese

Swedish Turkish

Traditional Chinese Ukrainian

Kensington lock VESA mount (100 x 100 mm)

DDC/CI Plug and Play Mac OS X Compatibility sRGB

Other convenience

Windows 10 / 8.1 / 8 / 7

Stand

-5/20 degree Tilt

Power

On mode 15.7 W (typ.) (EnergyStar 7.0 test method)

Standby mode 0.5 W (typ.) 0.5 W (typ.) Off mode Operation - White Power LED indicator

Standby mode - White (flashing)

Power supply

100-240 VAC, 50-60 Hz

Dimensions

(mm)

Product with stand

560 x 424 x 219 mm

Product without

stand (mm)

 0°C to 40°C $^{\circ}\text{C}$

-20°C to 60°C °C

20%-80% %

EnergyStar 7.0 EPEAT Silver

hour(s)

 RoHS

Lead-free

Packaging in mm (W

x H x D

608 x 419 x 121 mm

Weight

Product with stand 3.41 kg (kg) 3.02 kg

Product without stand (kg) Product with pack-

4.69 kg aging (kg)

Operating conditions

Temperature range (operation) Temperature range

(storage) Relative humidity

Altitude

MTBF

Sustainability

Environmental and energy

560 x 348 x 53 mm

Operation: +12,000 ft (3658 m), Non-

operation: +40,000 ft (12,192 m)

70,000 hrs (excluded backlight)

Recyclable packaging material

Mercury Free

100 %

Compliance and standards

Regulatory Approvals

CE Mark FCC Class B TCO certified cETLus TUV/ISO9241-307

BSMI PSB RCM UKRAINIAN **EPA**

CECP WEEE CCC

Cabinet

Colour Black

Hairline (front bezel)/Texture (rear Finish

cover)

What's in the box?

Monitor with stand

Cables

Yes D-Sub cable, Power cable

User Documentation

Yes



data subject to change 2018, September 7

Version: 1.0.1 EAN: 8712581745868 © 2018 Koninklijke Philips N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.