

LCD monitor with SmartControl Lite



- V Line
- 21.5" (54.6 cm)

223V5LHSB/27

Great LED images in vivid colors

Enjoy vivid LED pictures on this Philips display. Equipped with HDMI and SmartControl lite, it's a great choice!

Benefits

Vivid pictures every time

- LED technology for vivid colors
- Easy display performance tuning with SmartControl Lite
- SmartContrast for rich black details
- 16:9 Full HD display for best viewing experience

Experience multimedia

- HDMI-ready for Full HD entertainment

Great choice

- Mercury Free eco-friendly display
- Compact design saves space
- VESA mount allows for flexibility

Features

LED technology

White LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of LCD backlight, resulting in super high contrast ratio. It also gives superior color reproduction thanks to consistent brightness across the screen.

Color, Brightness, screen calibration, Multi-media, ID management, etc with the mouse.

SmartControl Lite

SmartControl Lite is the next generation 3D icon based GUI monitor control software. This allows user to fine-tune most parameters of the monitor like

PHILIPS

SmartContrast



SmartContrast is a Philips technology that analyzes the contents you are displaying, automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

16:9 Full HD



The Full HD screen has the widescreen resolution of 1920 x 1080p. This is the highest resolution of HD sources for the best possible picture quality. It is fully future proof as it supports 1080p signals from all sources, including the

most recent like Blu-ray and advanced HD game consoles. The signal processing is extensively upgraded to support this much higher signal quality and resolution. It produces brilliant flicker-free progressive scan pictures with superb brightness and colors.

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. A HDMI cable enables high-quality digital video and audio all transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).

Mercury Free

Philips monitors with LED backlighting are free of Mercury content, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its life-cycle, from manufacturing to disposal.

Specifications

Please note that this is a pre-sales leaflet. The contents of this leaflet reflect the best of our knowledge per date and country mentioned above. The contents of this leaflet are subject to change without notice. Philips does not accept any liability as to the contents of this leaflet.

Picture/Display

LCD panel type	TFT-LCD
Backlight type	W-LED system
Panel Size	21.5 inch / 54.6 cm
Effective viewing area	476.64 (H) x 268.11 (V)
Aspect ratio	16:9
Optimum resolution	1920 x 1080 @ 60 Hz
Response time (typical)	5 ms
Brightness	250 cd/m ²
SmartContrast	10,000,000:1
Contrast ratio (typical)	1000:1
Pixel pitch	0.248x0.248 mm
Viewing angle	170° (H) / 160° (V) @ C/R > 10
Display colors	16.7 M
Scanning Frequency sRGB	30 -83 kHz (H) / 56 -76 Hz (V) Yes

Connectivity

Signal Input	HDMI (digital, HDCP) VGA (Analog)
Sync Input	Separate Sync Sync on Green
Audio (In/Out)	HDMI audio out

Convenience

User convenience	Auto/Down 4:3 Wide/Up Brightness/Back Menu/OK Power On/Off
OSD Languages	Brazil Portuguese Czech Dutch English Finnish French German Hungarian Italian

Japanese	
Korean	
Polish	
Portuguese	
Russian	
Simplified Chinese	
Spanish	
Swedish	
Turkish	
Ukrainian	
Other convenience	Kensington lock VESA mount (100x100mm)
Plug & Play Compatibility	DDC/CI Mac OS X sRGB Windows 7 Windows 8

Stand

Tilt	-5/20 degree
------	--------------

Power

On mode	15.3 W (typ.) (EnergyStar 7.0 test method)
Standby mode	0.5 W
Off mode	0.5 W
Power LED indicator	Operation - White Standby mode- White (blinking)
Power supply	Built-in 100-240VAC, 50-60Hz

Dimensions

Product with stand (mm)	503 x 376 x 213 mm
Product with stand in inch	19.8 x 14.8 x 8.4 inch
Product without stand (mm)	503 x 316 x 50 mm
Product without stand in inch	19.8 x 12.4 x 2.0 inch
Packaging in mm (WxHxD)	555 x 414 x 107 mm

Packaging in inch (WxHxD) 21.9 x 16.3 x 4.21 inch

Weight

Product with stand (kg) 2.61 kg
Product with stand (lb) 5.74 lb
Product without stand (kg) 2.35 kg
Product without stand (lb) 5.17 lb
Product with packaging (kg) 3.87 kg
Product with packaging (lb) 8.51 lb

Operating conditions

Temperature range (operation) 0°C to 40°C °C
Temperature range (storage) -20°C to 60°C °C
Relative humidity 20%-80 %
Altitude Operation: +12,000ft (3,658m), Non-operation: +40,000ft (12,192m)
MTBF 30,000 hour(s)

Sustainability

Environmental and energy EnergyStar 7.0
EPEAT Silver
RoHS
Lead-free
Mercury Free
Recyclable packaging material 100 %

Compliance and standards

Regulatory Approvals BSMI
CE Mark
FCC Class B
GOST
PSB
SASO
SEMKO
TCO certified
TUV/ISO9241-307
cETLus
WEEE

Cabinet

Color Black
Finish Hairline (front bezel) / Texture (rear cover)



data subject to change
2018, September 6

Version: 2.0.1
UPC: 609585243514

© 2018 Koninklijke Philips N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com