

Philips Monitor USB-C monitor

**5000** series 27" (68.6 cm) 2560 x 1440 (QHD)

27E1N5600AE

# Simplify your connections with USB-C

This Philips USB-C multi-purpose monitor offers clutter-free setup. With a single cable you can view smooth high-resolution video, transfer data and charge your laptop. A true hub for mobile professionals.

#### Single cable USB-C connection

• Connect your notebook with one USB-C cable

### **Superb Picture Quality**

- IPS LED wide view technology for image and colour accuracy
- Crystal clear images with Quad HD 2560 x 1440 pixels
- 1 ms (MPRT) fast response for crisp images and smooth gameplay
- SmartImage game mode optimised for gamers
- SmartContrast for rich black details

#### Features designed for you

- LowBlue mode and Flicker-free easy-on-the eyes viewing
- Built-in stereo speakers for multimedia
- Tilt, pivot and adjust the height for an ideal viewing position
- EasyRead mode for a paper-like reading experience
- Cable management reduces cable clutter for a neat workspace
- · EasySelect menu toggle key for quick on-screen menu access



# Highlights

#### **USB-C** connection



This Philips display features a USB type-C connector with power delivery. With intelligent and flexible power management, you can power charge your compatible device directly. Its slim, reversible USB-C allows for easy, one-cable connection. You can watch high-resolution video and transfer data at super speed, while powering up and recharging your compatible device at the same time.

#### 1 ms MPRT fast response



MPRT (motion picture response time) is a more intuitive way to describe response time, which directly refers to the duration between seeing blurry noise and clean, crisp images. The Philips gaming monitor with 1 ms MPRT effectively eliminates smearing and motion blur and delivers sharper and more precise visuals to enhance your gaming experience. The best choice for playing thrilling and twitch-sensitive games.

### **CrystalClear images**



These Philips screens deliver Crystal Clear, Quad HD 2560 x 1440 or 2560 x 1080 pixel images. Utilising high-performance panels with high-density pixel count, enabled by high-bandwidth sources like Displayport, HDMI and Dual link DVI, these new displays will make your images and graphics come alive. Whether you are a demanding professional requiring extremely detailed information for CAD-CAM solutions, a user of 3D graphic applications or a financial wizard working on huge spreadsheets, Philips displays will give you Crystal Clear images.

## SmartImage Game mode



The new Philips gaming display has quick-access OSD fine-tuned for gamers, offering you multiple options. "FPS" mode (First person shooting) improves dark themes in games, allowing you to see hidden objects in dark areas. "Racing" mode adapts the display with the fastest response time and high colour, along with image adjustments. "RTS" mode (Real-time strategy) has a special SmartFrame mode that enables highlighting of specific area and allows for size and image adjustments. Gamer 1 and Gamer 2 enable you to save

personal customised settings based on different games, ensuring best performance.

#### LowBlue Mode and Flicker-free



Our LowBlue Mode and Flicker-free technology have been developed to reduce eye strain and fatigue often caused by long hours in front of a monitor.

#### **Built-in stereo speakers**



A pair of high-quality stereo speakers built into a display device. They may be visible front firing, or invisible down firing, top firing, rear firing etc. depending on model and design.

#### **Compact Ergo Base**



The Compact Ergo Base is a people-friendly Philips monitor base that tilts, pivot and height-adjusts so each user can position the monitor for maximum viewing comfort and efficiency.





















# **Specifications**

#### Picture/Display

- LCD panel type: IPS technology
- · Backlight type: W-LED system
- Panel Size: 27 inch/68.6 cm
- Display Screen Coating: Anti-Glare, 3H, Haze 25%
  Effective viewing area: 596.736 (H) x 335.664 (V)
- · Aspect ratio: 16:9
- Maximum resolution: 2560 x 1440 @ 75 Hz\*
- Pixel Density: 108.79 PPI
- Response time (typical): 4 ms (Grey to Grey)\*
- MPRT: 1 ms
- Brightness: 300 cd/m<sup>2</sup>
- · Contrast ratio (typical): 1000:1
- SmartContrast: Mega Infinity DCR
- Pixel pitch: 0.2331 x 0.2331 mm
   Viewing angle: 178° (H)/178° (V), @ C/R > 10
- Flicker-free
- Picture enhancement: SmartImage game
- Colour gamut (typical): NTSC 102.2%\*, sRGB 114.18%
- Display colours: 16.7 M
- Scanning Frequency: 30-114 kHz (H)/48-75 Hz
- · LowBlue Mode
- EasyRead
- sRGB
- · Adaptive sync

#### Connectivity

- Signal Input: HDMI 1.4 x 1, DisplayPort 1.2 x 1, USB-C 3.2 Gen 1 x 1 (upstream, Power Delivery up to 65 W)
- HDCP: HDCP 1.4 (HDMI/DisplayPort/USB-C)
- USB:: USB 3.2 x 4 (downstream with 1 fast charge B.C 1.2)
- Sync Input: Separate Sync
- Audio (In/Out): Audio out

- USB-C: Reversible plug connector
- · Super speed: Data and Video transfer
- DP: Built-in Display Port Alt mode
- Power delivery: USB PD version 3.0
- USB-C max. power delivery: Up to 65 W (5V/3A, 9V/3A, 10V/3A, 12V/3A, 15V/3A, 20V/3.25A)

#### **Convenience**

- Built-in Speakers: 3 W x 2
- User convenience: Power On/Off, Menu, Volume, Input, SmartImage Game
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
- Other convenience: Kensington lock, VESA mount  $(100 \times 100 \text{ mm})$
- · Plug and Play Compatibility: DDC/CI, Mac OS X,

sRGB, Windows 10 / 8.1 / 8 / 7

#### Stand

- · Height adjustment: 130 mm
- Pivot: -/+ 90 degree
- Tilt: -5/20 degree

- On mode: 29.1 W (typ.)
- Standby mode: 0.5 W (typ.)
- Off mode: 0.3 W (typ.)
- Energy Label Class: F
- · Power LED indicator: Operation White, Standby mode - White (flashing)
- Power supply: Internal, 100-240 VAC, 50-60 Hz

#### **Dimensions**

- Product with stand (max height):  $614 \times 510 \times$ 212 mm
- Product without stand (mm): 614 x 365 x 52 mm
- Packaging in mm (W x H x D): 780 x 525 x 186 mm

#### Weight

- Product with stand (kg): 6.56 kg
- Product without stand (kg): 4.70 kg
- Product with packaging (kg): 10.64 kg

#### **Operating conditions**

- Temperature range (operation): 0 to 40 °C
- Temperature range (storage): -20 to 60 °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000 ft (3658 m), Nonoperation: +40,000 ft (12,192 m)
- MTBF: 50,000 hrs (excluding backlight) hour(s)

#### Sustainability

- · Environmental and energy: RoHS
- Recyclable packaging material: 100 %
- Specific Substances: Mercury free, PVC/BFR free housing

#### Compliance and standards

 Regulatory Approvals: CB, CE Mark, CU-EAC, EAEU RoHS, FCC Class B, ICES-003, TUV/ ISO9241-307, TUV-BAUART

- · Colour: Black
- · Finish: Textured

## What's in the box?

- · Monitor with stand
- · Cables: HDMI cable, USB-C to USB-C cable, Power cable
- User Documentation

- "IPS" word mark / trademark and related patents on technologies belong to their respective owners
- The maximum resolution works for either HDMI input or DP input. \* For best output performance, please always ensure that your gra card is capable of achieving the maximum resolution and refresh rate of this Philips display.
- Response time value equal to SmartResponse
- \* MPRT adjusts the brightness for blur reduction, so the brightness cannot be adjusted while MPRT is turned on. To reduce motion blur, the LED backlight will strobe in time with the screen refresh rate, which may cause a noticeable change in brightness.
- \* MPRT is a gaming-optimised mode. Turning on MPRT may cause noticeable screen flickering. It is recommended to turn this mode off when you are not using the gaming function.
  \* NTSC Area based on CIE 1976

- \* sRGB Area based on CIE1931 \* For USB-C power and charging function, your Notebook/device must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more
- For Video transmission via USB-C, your Notebook/device must support USB-C DP Alt mod
- \* The monitor may look different from feature images.



Issue date 2022-04-21

Version: 3.1.1

12 NC: 8670 001 80249 EAN: 87 12581 78341 9 © 2022 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com